

**FILA INDUSTRIA CHIMICA S.P.A.**

Revision nr. 1

Dated 17/06/2022

MULTI SURFACE STAIN REMOVER

Printed on 03/11/2022

Page n. 1/16

First Issue

Safety data sheet compliant with regulation (EC) no. 1907/2006 (REACH), Annex II, and subsequent amendments introduced by Commission Regulation (EU) no. 2020/878

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

MULTI SURFACE STAIN REMOVER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

Cleaner, degreaser and wax remover.

Identified Uses

Industrial

Professional

Consumer

Uses

-

✓

✓

1.3. Details of the supplier of the safety data sheet

Name

FILA INDUSTRIA CHIMICA S.P.A.

Full address

Via Garibaldi, 58

District and Country

35018 San Martino di Lupari (PD)**ITALIA****Tel. +39.049.9467300****Fax +39.049.9460753**

e-mail address of the competent person

responsible for the Safety Data Sheet

Supplier:

sds@filasolutions.com**FILA SURFACE CARE PRODUCTS****LIMITED****12 Bridewell Place,****Third Floor East,****London****EC4V 6AP**

1.4. Emergency telephone number

For urgent inquiries refer to

TEL +39.049.9467300 (Monday –**Friday; 8.30 - 12.30 and 14.00 - 17.30)****UNITED KINGDOM: NHS Direct 111 (In England, Scotland North Ireland) 08454647****(Wales)****IRELAND 018092166**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2

H319

Causes serious eye irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

**FILA INDUSTRIA CHIMICA S.P.A.**

Revision nr. 1

Dated 17/06/2022

Printed on 03/11/2022

Page n. 2/16

First Issue

MULTI SURFACE STAIN REMOVER

Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.

Precautionary statements:

P102 Keep out of reach of children.
P101 If medical advice is needed, have product container or label at hand.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear eye protection / face protection.
P337+P313 If eye irritation persists: Get medical advice / attention.
P264 Wash hands thoroughly after handling.

Ingredients according to Regulation (EC) No. 648/20045% or over but less than soap
15%

perfumes, Coumarin, Limonene, Linalool

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.
The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients**3.1. Substances**

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Phenylmethanol CAS 100-51-6 EC 202-859-9 INDEX 603-057-00-5 REACH Reg. 01-2119492630-38	$14 \leq x < 19$	Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319 LD50 Oral: 1620 mg/kg, STA Inhalation vapours: 11 mg/l
Propylene glycol n-propyl ether CAS 1569-01-3 EC 216-372-4 INDEX - REACH Reg. 01-2119474443-37	$4 \leq x < 5$	Flam. Liq. 3 H226, Eye Irrit. 2 H319
Monoethanolamine oleate CAS 2272-11-9 EC 218-878-0 INDEX - REACH Reg. esente in accordo all'Alil. V del REACH.	$1 \leq x < 2$	Eye Irrit. 2 H319
ETHANOLAMINE CAS 141-43-5 EC 205-483-3 INDEX 603-030-00-8	$0,6 \leq x < 0,7$	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Chronic 3 H412 STOT SE 3 H335: $\geq 5\%$ LD50 Oral: 1515 mg/kg, STA Dermal: 1100 mg/kg, STA Inhalation vapours:



MULTI SURFACE STAIN REMOVER

11 mg/l, STA Inhalation mists/powders: 1,5 mg/l

REACH Reg. 01-2119486455-28

(1S)6,6-DIMETHYL-2-METHYLENBICYCLOHEPTANE

CAS 127-91-3

 $0 \leq x < 0,02$

Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 204-872-5

INDEX -

REACH Reg. 01-2119519230-54

Benzyl acetate

CAS 140-11-4

 $0 \leq x < 0,02$

Aquatic Chronic 3 H412

EC 205-399-7

INDEX -

REACH Reg. 01-2119638272-42

pin-2 (3) -ene

CAS 80-56-8

 $0 \leq x < 0,02$

Flam. Liq. 3 H226, Acute Tox. 4 H302, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Skin Sens. 1B H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 201-291-9

INDEX -

REACH Reg. 01-2119519223-49-

0000

LD50 Oral: 500 mg/kg

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove any contact lenses. Wash immediately with plenty of warm water for at least 30/60 minutes, opening the eyelids well. Consult a doctor immediately.

SKIN: Remove contaminated clothing. Take a shower immediately. Consult a doctor immediately.

INGESTION: Consult a doctor immediately. Do not induce vomiting unless expressly authorized by your doctor.

INHALATION: Call a doctor immediately. Bring the subject to fresh air, away from the accident site. If breathing stops, give artificial respiration. Take appropriate precautions for the rescuer.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact: causes burns, pain, watery eyes, redness.

Ingestion: may cause heartburn, throat and stomach.

Inhalation: cough and irritation of the respiratory tract.

Skin contact: burns, pain or irritation, redness and blistering.

4.3. Indication of any immediate medical attention and special treatment needed

Utile urgent medical intervention. Treat symptomatically.

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.


5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

	FILA INDUSTRIA CHIMICA S.P.A.	Revision nr. 1
	MULTI SURFACE STAIN REMOVER	Dated 17/06/2022 Printed on 03/11/2022 Page n. 4/16 First Issue

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)


See section 01 for defined uses. There are no particular uses.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ «σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία»»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdi og grenseverdi for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdi), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos

	FILA INDUSTRIA CHIMICA S.P.A.	Revision nr. 1
	MULTI SURFACE STAIN REMOVER	Dated 17/06/2022 Printed on 03/11/2022 Page n. 5/16 First Issue

POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

BENZYL ALCOHOL

Threshold Limit Value


Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	CZE	40	8,88	80	17,76		
AGW	DEU	22	5	44	10	SKIN	11
HTP	FIN	45	10				
NDS/NDSch	POL	240					
MV	SVN	22	5	44	10	SKIN	
Predicted no-effect concentration - PNEC							
Normal value in fresh water				1	mg/l		
Normal value in marine water				0,1	mg/l		
Normal value for fresh water sediment				5,27	mg/kg		
Normal value for marine water sediment				0,527	mg/kg		
Normal value for water, intermittent release				2,3	mg/l		
Normal value of STP microorganisms				39	mg/l		
Normal value for the terrestrial compartment				0,45	mg/kg		


Health - Derived no-effect level - DNEL / DMEL


Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	20 mg/kg bw/d		4 mg/kg bw/d				
Inhalation	VND	27 mg/m3		5,4 mg/m3	VND	110 mg/m3	VND	22 mg/m3
Skin	VND	20 mg/kg bw/d	VND	4 mg/kg bw/d	VND	40 mg/kg bw/d	VND	8 mg/kg bw/d

1-propoxypropan-2-ol

Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,1	mg/l			
Normal value in marine water				0,01	mg/l			
Normal value for fresh water sediment				0,386	mg/kg			
Normal value for marine water sediment				0,0386	mg/kg			

		FILA INDUSTRIA CHIMICA S.P.A.				Revision nr. 1		
		MULTI SURFACE STAIN REMOVER				Dated 17/06/2022		
						Printed on 03/11/2022		
						Page n. 6/16		
						First Issue		
Normal value for water, intermittent release		1		mg/l				
Normal value of STP microorganisms		4		mg/l				
Normal value for the terrestrial compartment		0,0185		mg/kg				
Health - Derived no-effect level - DNEL / DMEL								
		Effects on consumers			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			VND	26 mg/m3			VND	217 mg/m3
Skin			VND	2,2 mg/kg/d			VND	9 mg/kg/d
Monoethanolamine oleate								
Predicted no-effect concentration - PNEC								
Normal value in fresh water		0,478		mg/l				
Normal value in marine water		0,0478		mg/l				
Normal value for fresh water sediment		8020		mg/kg				
Normal value for marine water sediment		802		mg/kg				
Normal value for water, intermittent release		0,141		mg/l				
Normal value of STP microorganisms		0,562		mg/l				
Normal value for the terrestrial compartment		1600		mg/kg				
Health - Derived no-effect level - DNEL / DMEL								
		Effects on consumers			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	25 mg/kg bw/d						
Inhalation			VND	43,5 mg/m3			VND	146,9 mg/m3
Skin			VND	25 mg/kg bw/d			VND	41,7 mg/kg bw/d
ETHANOLAMINE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	CZE	2,5	0,985	7,5	2,955			
AGW	DEU	0,5	0,2	0,5	0,2	SKIN		
MAK	DEU	0,51	0,2	0,51	0,2			
TLV	DNK	2,5	1			SKIN	E	
VLA	ESP	2,5	1	7,5	3	SKIN		
VLEP	FRA	2,5	1	7,6	3	SKIN		
HTP	FIN	2,5	1	7,6	3	SKIN		
TLV	GRC	2,5	1	7,6	3			
AK	HUN	2,5		7,6		SKIN		
GVI/KGVI	HRV	2,5	1	7,6	3	SKIN		
VLEP	ITA	2,5	1	7,6	3	SKIN		
TLV	NOR	2,5	1			SKIN		
TGG	NLD	2,5		7,6		SKIN		

		FILA INDUSTRIA CHIMICA S.P.A.				Revision nr. 1		
		MULTI SURFACE STAIN REMOVER				Dated 17/06/2022 Printed on 03/11/2022 Page n. 7/16 First Issue		
VLE	PRT	2,5	1	7,6	3	SKIN		
NDS/NDSch	POL	2,5		7,5		SKIN		
TLV	ROU	2,5	1	7,6	3	SKIN		
NGV/KGV	SWE	2,5	1	7,5	3	SKIN		
NPEL	SVK	2,5	1	7,6	3	SKIN		
MV	SVN	2,5	1	7,6	3	SKIN		
ESD	TUR	2,5	1	7,6	3	SKIN		
WEL	GBR	2,5	1	7,6	3	SKIN		
OEL	EU	2,5	1	7,6	3	SKIN		
TLV-ACGIH		7,5	3	15	6			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,085		mg/l		
Normal value in marine water				0,0085		mg/l		
Normal value for fresh water sediment				0,434		mg/kg		
Normal value for marine water sediment				0,0434		mg/kg		
Normal value for water, intermittent release				0,028		mg/l		
Normal value of STP microorganisms				100		mg/l		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	3,75 mg/kg/d				
Inhalation			2 mg/m3	VND			3,3 mg/m3	VND
Skin			VND	0,24 mg/kg/d			VND	1 mg/kg/d
(1S)6,6-DIMETHYL-2-METHYLENBICYCLOHEPTANE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
OEL	EU		20					
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation								5,98 mg/m3
Benzyl acetate								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
OEL	EU		10					
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,004		mg/l		
Normal value in marine water				0,0004		mg/l		

	FILA INDUSTRIA CHIMICA S.P.A.	Revision nr. 1
	MULTI SURFACE STAIN REMOVER	Dated 17/06/2022 Printed on 03/11/2022 Page n. 8/16 First Issue

Normal value for fresh water sediment					0,114	mg/kg			
Normal value for water, intermittent release					8,55	mg/l			
Normal value for the terrestrial compartment					0,0205	mg/kg			
Health - Derived no-effect level - DNEL / DMEL									
	Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Oral						6,25 mg/kg bw/d		3,125 mg/kg bw/d	
Inhalation		11 mg/m3		5,5 mg/m3		43,8 mg/m3		21,9 mg/m3	
Skin		6,25 mg/kg bw/d		3,125 mg/kg bw/d		12,5 mg/kg bw/d		6,25 mg/kg bw/d	
pin-2 (3) -ene									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
OEL	EU		20						
Health - Derived no-effect level - DNEL / DMEL									
	Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Inhalation								5,98 mg/m3	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect your hands with category III work gloves (ref. Standard EN 374).

For the final choice of material for work gloves, the following must be considered: compatibility, degradation, breakage time and permeation.

In the case of preparations, the resistance of work gloves to chemical agents must be checked before use as it is unpredictable. Gloves have a wear time that depends on the duration and method of use

Chemical resistant gloves are recommended. Recommended materials: PVC, Neoprene, Natural rubber, Butyl rubber, minimum thickness 0.71 mm or a material with protective barrier with high performance level for continuous contact conditions, minimum permeation / rupture in 480 minutes according to the CEN, EN420 and EN 374 standards.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of

**MULTI SURFACE STAIN REMOVER**

various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	liquid	
Colour	Light yellow	
Odour	Pine fragrance	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not applicable	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	10,8	
Kinematic viscosity	not available	
Solubility	Readily soluble	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	not available	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information**9.2.1. Information with regard to physical hazard classes**

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	20,02 %
VOC (volatile carbon)	19,61 %
Explosive properties	not applicable
Oxidising properties	not applicable

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.



FILA INDUSTRIA CHIMICA S.P.A.

Revision nr. 1

Dated 17/06/2022

Printed on 03/11/2022

Page n. 10/16

First Issue

MULTI SURFACE STAIN REMOVER

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F. Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid, iron, oxidising agents, sulphuric acid. Risk of explosion on contact with: phosphorus trichloride.

ETHANOLAMINE

May react dangerously with: acrylonitrile, chloroepoxypropane, chlorosulphuric acid, hydrogen chloride, iron-sulphur compounds, acetic acid, acetic anhydride, mesityl oxide, nitric acid, sulphuric acid, strong acids, vinyl acetate, cellulose nitrate.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

BENZYL ALCOHOL

Avoid exposure to: air, sources of heat, naked flames.

ETHANOLAMINE

Avoid exposure to: air, sources of heat.

10.5. Incompatible materials

Oxidizing agents. Strong acids and bases.

BENZYL ALCOHOL

Incompatible with: sulphuric acid, oxidising substances, aluminium.

ETHANOLAMINE

Incompatible with: iron, strong acids, strong oxidants.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHANOLAMINE

May develop: nitric oxide, carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:

> 20 mg/l

ATE (Oral) of the mixture:

> 2000 mg/kg

ATE (Dermal) of the mixture:

Not classified (no significant component)

**MULTI SURFACE STAIN REMOVER****BENZYL ALCOHOL**

LD50 (Dermal): 2000 mg/kg coniglio
LD50 (Oral): 1620 mg/kg ratto maschio
LC50 (Inhalation vapours): > 4,178 mg/l/4h Ratto (OCSE403)
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

1-propoxypropan-2-ol

LD50 (Dermal): > 2000 mg/kg Rat
LD50 (Oral): > 2000 mg/kg Rat

Monoethanolamine oleate

LD50 (Dermal): 2504 mg/kg male rabbit
LD50 (Oral): 1089 mg/kg rat male/female
LC50 (Inhalation vapours): > 1,3 mg/l/4h 6h rat male/female

ETHANOLAMINE

LD50 (Dermal): 2504 mg/kg male rabbit
STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral): 1515 mg/kg rat male/female

pin-2 (3) -ene

LD50 (Oral): 500 mg/kg

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE



FILA INDUSTRIA CHIMICA S.P.A.

Revision nr. 1

Dated 17/06/2022

Printed on 03/11/2022

Page n. 12/16

First Issue

MULTI SURFACE STAIN REMOVER

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

1-propoxypropan-2-ol

LC50 - for Fish

> 100 mg/l/96h Rainbow Trout

EC50 - for Crustacea

> 100 mg/l/48h Daphnia Magna

ETHANOLAMINE

LC50 - for Fish

349 mg/l/96h Cyprinus carpio

EC50 - for Crustacea

65 mg/l/48h Daphnia Magna

EC50 - for Algae / Aquatic Plants

2,1 mg/l/72h Pseudokirchnerella subcapitata

Chronic NOEC for Fish

1,24 mg/l 41d Oryzias latipes

BENZYL ALCOHOL

LC50 - for Fish

460 mg/l/96h Pimephales promelas

EC50 - for Crustacea

230 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants

770 mg/l/72h Pseudokirchnerella subcapitata

Monoethanolamine oleate

LC50 - for Fish

349 mg/l/96h Cyprinus carpio

EC50 - for Crustacea

65 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants

2,5 mg/l/72h Pseudokirchnerella subcapitata

pin-2 (3) -ene

EC50 - for Crustacea

475 mg/l/48h

Chronic NOEC for Crustacea

2 mg/l

Chronic NOEC for Algae / Aquatic Plants

131 mg/l

12.2. Persistence and degradability

1-propoxypropan-2-ol

Rapidly degradable

>70% 10d

ETHANOLAMINE

Solubility in water

1000 - 10000 mg/l

Rapidly degradable

>70% 28d

**FILA INDUSTRIA CHIMICA S.P.A.**

Revision nr. 1

Dated 17/06/2022

MULTI SURFACE STAIN REMOVER

Printed on 03/11/2022

Page n. 13/16

First Issue

BENZYL ALCOHOL
Rapidly degradable
92-96% 14d OECD301C
92-96% 14d OECS301C
Monoethanolamine oleate
Rapidly degradable
>90% 21d

12.3. Bioaccumulative potential

ETHANOLAMINE
Partition coefficient: n-octanol/water -2,3

BENZYL ALCOHOL
Partition coefficient: n-octanol/water 1,05

12.4. Mobility in soil

ETHANOLAMINE
Partition coefficient: soil/water -0,5646

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user



FILA INDUSTRIA CHIMICA S.P.A.

Revision nr. 1

Dated 17/06/2022

Printed on 03/11/2022

Page n. 14/16

First Issue

MULTI SURFACE STAIN REMOVER

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

Phenylmethanol

Propylene glycol n-propyl ether

ETHANOLAMINE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3

Flammable liquid, category 3

Acute Tox. 4

Acute toxicity, category 4

Asp. Tox. 1

Aspiration hazard, category 1



MULTI SURFACE STAIN REMOVER

Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament



FILA INDUSTRIA CHIMICA S.P.A.

Revision nr. 1

Dated 17/06/2022

MULTI SURFACE STAIN REMOVER

Printed on 03/11/2022

Page n. 16/16

First Issue

7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

- The Merck Index. - 10th Edition

- Handling Chemical Safety

- INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

- IFA GESTIS website

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for the user:

The information contained in this sheet is based on the knowledge available to us at the date of the latest version. The user must ensure the suitability and completeness of the information in relation to the specific use of the product.

This document should not be construed as a guarantee of any specific property of the product.

Since the use of the product does not fall under our direct control, it is the user's obligation to observe the laws and regulations in force regarding hygiene and safety under his own responsibility. No responsibility is assumed for improper use.

Provide adequate training to personnel assigned to the use of chemical products.

This safety data sheet has been prepared by a competent technician who has received suitable training.

METHODS OF CALCULATING THE CLASSIFICATION

Physico-chemical hazards: The classification of the product was derived from the criteria established by the CLP Regulation Annex I Part 2. The methods for assessing the physico-chemical properties are reported in section 9.

Health hazards: The classification of the product is based on the calculation methods set out in Annex I of CLP Part 3, unless otherwise indicated in section 11.

Environmental hazards: The classification of the product is based on the calculation methods set out in Annex I of CLP Part 4, unless otherwise indicated in section 12.

Method of assessing the information referred to in Article 9 of Regulation (EC) No. 1272/2008 which was used for classification purposes: calculation method.

First Issue