	FILA INDUSTRIA C	HIMICA S.P.A.	Revision nr. 1
	PORCELAIN CEMENT RI	ESIDDUE REMOVI	ER Printed on 03/11/2022 Page n. 1/13 First Issue
(REAČH), Ann Coi	heet compliant with ex II, and subseque mmission Regulation ording to Annex II to REACH - Regulation 20	nt amendmen n (EU) no. 202	ts introduced by 20/878
SECTION 1. Identification	n of the substance/mixture an	d of the company/u	Indertaking
1.1. Product identifier Product name	PORCELAIN CEMENT	RESIDDUE REMOVER	
	e substance or mixture and uses advised ng acid grout residue remover and limes	0	
Identified Uses Uses	Industrial	Professional	Consumer
Uses	~	~	~
1.3. Details of the supplier of the s Name Full address District and Country	FILA INDUSTRIA CHIM Via Garibaldi, 58 35018 San Martino di L ITALIA Tel. +39.049.9467300		
	Fax +39.049.9460753		
e-mail address of the competent pers responsible for the Safety Data Shee Supplier:			
1.4. Emergency telephone number For urgent inquiries refer to	TEL +39.049.9467300 (Friday; 8.30 - 12.30 ar	nd 14.00 - 17.30)	Scotland North Ireland) 08454647
SECTION 2. Hazards ider	ntification		
supplements). The product thus require		e provisions of (EU) Regulati	
Hazard classification and indication:			
Serious eye damage, category 1	H318	Causes serious eye	damage.
The classification of the compound, fea	aturing an extreme pH value, is based on th	ne results of an appropriate ir	n vitro test.
2.2. Label elements Hazard labelling pursuant to EC Regul	lation 1272/2008 (CLP) and subsequent arr	nendments and supplements	

FIR		FIL	A INDUSTRIA CHIMICA S.P.A.	Revision nr. 1
surface care solutions				Dated 17/03/2022
		PORCELA	AIN CEMENT RESIDDUE REMOVER	Printed on 03/11/2022 Page n. 2/13 First Issue
				1 1151 15500
Hazard pictograms:				
Signal words:	Danger			
Hazard statements:				
H318	Causes s	erious eye damage	Э.	
Precautionary statements:				
P101 P102 P280 P305+P351+P338 P310	Keep out Wear eye IF IN EYE rinsing.	of reach of children protection / face p	rotection. y with water for several minutes. Remove contact lenses, if	present and easy to do. Continue
Contains:	sulphami	dic acid		
Ingredients according to Re				
Less than 5%		surfactants		
2.3. Other hazards			ain any PBT or vPvB in percentage ≥ than 0,1%.	
The product does not conta	in substand	ces with endocrine	disrupting properties in concentration $\geq 0.1\%$.	
SECTION 3. Com	position	/information	on ingredients	
3.1. Substances				
nformation not relevant				
3.2. Mixtures				
Contains:				
Identification sulphamidic acid		x = Conc. %	Classification (EC) 1272/2008 (CLP)	
CAS 5329-14-6		10 ≤ x < 15	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Aquatic Chronic 3 H	1412
EC 226-218-8				
INDEX 016-026-00-0 REACH Reg. 01-211948	8633-28			
REAGINES. 01-211340	00000-20			
DIPROPYLENE GLYCOL MONOMETHYL ETHER CAS 34590-94-8	-	3≤x< 4	Eve Irrit. 2 H319	
	-	3≤x< 4	Eye Irrit. 2 H319	
MONOMETHYL ETHER CAS 34590-94-8	-	3≤x< 4	Eye Irrit. 2 H319	
MONOMETHYL ETHER CAS 34590-94-8 EC 252-104-2 INDEX - REACH Reg. 01-211945	50011-60	3≤x< 4	Eye Irrit. 2 H319	
MONOMETHYL ETHER CAS 34590-94-8 EC 252-104-2 INDEX -	50011-60	3≤x< 4 1≤x< 2	Eye Irrit. 2 H319 Acute Tox. 4 H302, Eye Dam. 1 H318, Aquatic Chronic	3 H412
MONOMETHYL ETHER CAS 34590-94-8 EC 252-104-2 INDEX - REACH Reg. 01-211945 Alcohols, secondary C1 ethoxylated	50011-60			3 H412
MONOMETHYL ETHER CAS 34590-94-8 EC 252-104-2 INDEX - REACH Reg. 01-211945 Alcohols, secondary C1 ethoxylated CAS 68131-40-8	50011-60		Acute Tox. 4 H302, Eye Dam. 1 H318, Aquatic Chronic	3 H412

FILA INDUSTRIA CHIMICA S.P.A.

Revision nr. 1

Dated 17/03/2022

PORCELAIN CEMENT RESIDDUE REMOVER

Page n. 3/13 First Issue

INDEX -

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove any contact lenses. Wash immediately and abundantly with lukewarm water for at least 30/60 minutes, opening the eyelids well. Consult a physician immediately.

SKIN: Take off contaminated clothing. Have a shower. Get medical attention if irritation persists.

INGESTION: Get medical attention immediately. Do not induce vomiting unless expressly authorized by your doctor.

INHALATION: Take the person to the open air, away from the place of the accident. If breathing stops, give artificial respiration and call a physician. Take adequate precautions for the rescuer.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not

Revision nr. 1

Dated	17/03/2022
Duiou	11/00/2022

PORCELAIN CEMENT RESIDDUE REMOVER

Page n. 4/13

Printed on 03/11/2022

First Issue

eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

FIX

See section 01 for defined uses. No other particular uses are foreseen.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH
		HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή
		ην προστασία των εργαζομένων από τους κινουνούς που συνσεονται με την εκσεόη σε καρκινογονούς η μεταλλαξιγόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők
HON	Magyarorszag	hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	narasanak kutat mankavanalok ogoszszejenek es zaliztonasątan vedenneto. Pravilnik o izmjenama i dopunama Pravilnika o zašiti radnika od izloženosti opasnimkemikalijama na radu.
	in valora	graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i
	0	arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum si pentru modificarea
		si completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
TUR	Türkiye	, Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2004/37/EC; Directive 98/24/EC; Directive 91/322/EEC.

sulphamidic acid

Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,048	mg/l
Normal value in marine water	0,0048	mg/l
Normal value for fresh water sediment	0,173	mg/kg
Normal value for marine water sediment	0,0173	mg/kg

								1	
			FILA INI	DUSTRIA	CHIMICA	S.P.A.		Revision nr. 1	
								Dated 17/03/2022	
		POF			RESIDDU		/FR	Printed on 03/11/2022	
								Page n. 5/13	
								First Issue	
		1							
Normal value for water, intermitter	nt releas	e			0,48	mg	g/l		
Normal value of STP microorganis	sms				2	mg	g/l		
Normal value for the food chain (s	econdar	ry poisonin	g)		0,00638	mg	g/kg		
Normal value for the terrestrial cor	mpartme	ent			0,638	mg	g/kg		
Health - Derived no-effect le	evel - D Effects consu	s on	1EL			Effects on workers			
Route of exposure	Acute		Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
Oral				VND	systemic 1,06 mg/kg bw/d		systemi	C	systemic
Skin				VND	5 mg/kg bw/d			VND	10 mg/kg bw/d
DIPROPYLENE GLYCOL MC	ONOME	ETHYL ET	THER						
Туре	Count	ry	TWA/8h		STEL/15min			narks /	
			mg/m3	ppm	mg/m3	ppm	Obs	ervations	
TLV	CZE		270	43,74	550	89,1	SKI	N	
AGW	DEU		310	50	310	50			
MAK	DEU		310	50	310	50			
TLV	DNK		309	50			SKI	N E	
VLA	ESP		308	50			SKI	N	
VLEP	FRA		308	50			SKI	N	
HTP	FIN		310	50			SKI	N	
TLV	GRC		600	100	900	150			
AK	HUN		308						
GVI/KGVI	HRV		308	50			SKI	N	
VLEP	ITA		308	50			SKI	N	
TLV	NOR		300	50			SKI	N	
TGG	NLD		300						
VLE	PRT		308	50			SKI	N	
NDS/NDSCh	POL		240		480		SKI	N	
TLV	ROU		308	50			SKI	N	
NGV/KGV	SWE		300	50	450 (C)	75 (C)	SKI	N	
NPEL	SVK		308	50			SKI	N	
MV	SVN		308	50			SKI	N	
ESD	TUR		308	50			SKI	N	
WEL	GBR		308	50			SKI	N	
OEL	EU		308	50			SKI	N	
Predicted no-effect concentration	- PNEC								
Normal value in fresh water					19	mg	g/l		

Normal value for marine water sediment 7,02

Normal value in marine water

Normal value for fresh water sediment

mg/l

mg/kg

mg/kg

1,9

70,2

Revision nr. 1

PORCELAIN CEMENT RESIDDUE REMOVER

Dated 17/03/2022 Printed on 03/11/2022

Page n. 6/13

First Issue

Normal value for water, int	ermittent release		190	m	g/I			
Normal value of STP micro	oorganisms			4168	m	g/I		
Normal value for the terres	trial compartment			2,74	m	g/kg		
Health - Derived no-ef		MEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
		···· ·		systemic		systemic		systemic
Oral			VND	36 mg/kg				
				bw/d				
Inhalation			VND	37,2 mg/m3			VND	308 mg/m3
				, J -				5 -
Skin			VND	121 mg/kg			VND	283 mg/kg/d
				bw/d				

Legend:

FIN

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Generally not necessary. In case of prolonged contact protect hands with category I work gloves (ref. Standard EN 374). Recommended material: Nitrile, minimum 0.38 mm thick or equivalent protective barrier material with a high level performance for conditions of use in continuous contact, with a minimum permeability time of 480 minutes in accordance with the CEN standard EN 420 and EN 374.

SKIN PROTECTION

Generally not necessary. In case of prolonged contact, wear category I work clothes with long sleeves and safety footwear for professional use (ref. Regulation 2016/425 and standard EN ISO 20344). Wash with soap and water after removing protective clothing.

EYE PROTECTION Wear airtight protective goggles (ref. Standard EN 166).

6 T 6 66 (

RESPIRATORY PROTECTION

Generally not necessary for normal use. In case of aerosol formation or exceeding the threshold value (e.g. TLV-TWA) of the substance or one or more of the substances present in the product, it is recommended to wear a mask with type A filter combined with type P filter (ref. standard EN 14387). The use of respiratory protection means is necessary in case the technical measures adopted are not sufficient to limit the exposure of the worker to the threshold values taken into consideration. The protection offered by the masks is however limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Appearance	Value liquid	Information
Colour	transparent	
Odour	characteristic	



Revision nr. 1

Dated 17/03/2022 Printed on 03/11/2022

PORCELAIN CEMENT RESIDDUE REMOVER

Page n. 7/13 First Issue

Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not applicable	
Lower explosive limit Upper explosive limit Flash point	not available not available > 60 °C	Reason for missing data:not explosive Reason for missing data:not explosive
Auto-ignition temperature pH	not available 0,8	Reason for missing data:not self-igniting
Kinematic viscosity	not available	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,072	
Relative vapour density	not available	
Particle characteristics	not applicable	
9.2. Other information		
9.2.1. Information with regard to physical haza	ard classes	
Information not available		
9.2.2. Other safety characteristics		
VOC (Directive 2010/75/EU)	3,00 % - 32,16 g/litre	

VOC (volatile carbon)	1,70 % - 18,23	g/litre
Explosive properties	not explosive	
Oxidising properties	not oxidizing	
Oxidising properties	hot oxidizing	

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

.

10.6. Hazardous decomposition products

Due to thermal decomposition or in case of fire, gases and vapors can be released that are potentially harmful to health.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

CLASSIFICATION METHOD:

Method for evaluating the information referred to in Article 9 of Regulation (EC) No. 1272/2008 which was used for classification purposes: expert judgment and proprietary experimental data.

Metabolism, toxicokinetics, mechanism of action and other information

	FILA INDUSTRIA CHIMICA	A S.P.A. Revision nr. 1	
		Dated 17/03/2022	l
	PORCELAIN CEMENT RESIDDU	JE REMOVER Printed on 03/11/2022	
		Page n. 8/13	
		First Issue	
nformation not available <u>nformation on likely routes of exposure</u> nformation not available <u>Delayed and immediate effects as well</u> <u>nformation not available</u> <u>nteractive effects</u> nformation not available <u>ACUTE TOXICITY</u>	as chronic effects from short and long-term exposure		
ATE (Inhalation) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture:	Not classified (no significan >2000 mg/kg Not classified (no significan		
sulphamidic acid			
LD50 (Oral): LD50 (Dermal):	3160 mg/kg ratto > 2000 mg/kg ratto		
DIPROPYLENE GLYCOL MONOMET	HYL ETHER		
LD50 (Oral):	2410 mg/kg mouse male (fa	asted)	

LD50 (Oral): LD50 (Dermal): LC50 (Inhalation vapours):

Alcohols, secondary C11-15, ethoxylated

STA (Oral):

500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION Proprietary test according to OECD guideline n. 404 performed on rabbit in GLP (OECD, 1998). During the initial single animal test and the confirmatory test, the test object did not cause any skin reactions in the rabbits tested in the form of application site erythema or edema as observed at 1 hour, 24, 48 and 72 hours after removing the patch.

2764 mg/kg rabbit > 29 ppm/1h 2h rat

Based on the "Primary Irritation Index" of zero (0.00) observed in this study, and as defined in the evaluation criteria, the product was found to be nonirritating to rabbit skin. No skin reactions were observed in this study at 24, 48 and 72 hours after patch removal.

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION Does not meet the classification criteria for this hazard class

Respiratory sensitization Information not available

Skin sensitization Information not available

GERM CELL MUTAGENICITY Does not meet the classification criteria for this hazard class

CARCINOGENICITY Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility Information not available

Revision nr. 1

PORCELAIN CEMENT RESIDDUE REMOVER

Dated 17/03/2022 Printed on 03/11/2022

Page n. 9/13 First Issue

Adverse effects on development of the offspring Information not available

Effects on or via lactation Information not available

FIR

<u>STOT - SINGLE EXPOSURE</u> Does not meet the classification criteria for this hazard class

Target organs Information not available

Route of exposure Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs Information not available

Route of exposure Information not available

ASPIRATION HAZARD Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

12.1. Toxicity

Alcohols, secondary C11-15, ethoxylated EC50 - for Algae / Aquatic Plants	5,2 mg/l/72h Selenastrum sp.
DIPROPYLENE GLYCOL MONOMETHYL ETHER LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants	1300 mg/l/96h Lepomis machrochirus > 1919 mg/l/48h Daphnia magna > 969 mg/l/72h Scenedesmus subspicatus
sulphamidic acid LC50 - for Fish	70,3 mg/l/96h pimephales promelas
12.2. Persistence and degradability	
Alcohols, secondary C11-15, ethoxylated Rapidly degradable 65% 28 d DIPROPYLENE GLYCOL MONOMETHYL ETHER Solubility in water Rapidly degradable 85% 28d	1000 - 10000 mg/l
12.3. Bioaccumulative potential	
DIPROPYLENE GLYCOL MONOMETHYL ETHER Partition coefficient: n-octanol/water	0,056
12.4. Mobility in soil	

Revision nr. 1

Dated 17/03/2022

Printed on 03/11/2022

PORCELAIN CEMENT RESIDDUE REMOVER

Page n. 10/13 First Issue

Information not available

FIN

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number not applicable

14.2. UN proper shipping name not applicable

14.3. Transport hazard class(es) not applicable

14.4. Packing group not applicable

14.5. Environmental hazards not applicable

14.6. Special precautions for user not applicable

14.7. Maritime transport in bulk according to IMO instruments Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point	3
Contained substance	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

	FILA INDUSTRIA CHIMICA S.P.A.	Revision nr. 1
		Dated 17/03/2022
	PORCELAIN CEMENT RESIDDUE REMOVER	Printed on 03/11/2022
		Page n. 11/13
		First Issue
None <u>Substances subject to exportation re</u> None <u>Substances subject to the Rotterdan</u>	porting pursuant to Regulation (EU) 649/2012:	
None		
Substances subject to the Stockholn None	n Convention:	
Healthcare controls		
	gent must not undergo health checks, provided that available risk-assessment of st and that the 98/24/EC directive is respected.	data prove that the risks related to the

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

sulphamidic acid

DIPROPYLENE GLYCOL MONOMETHYL ETHER

SECTION 16. Other information

CLASSIFICATION METHOD:

Method of evaluating the information referred to in Article 9 of Regulation (EC) no. 1272/2008 which was used for classification purposes: expert judgment and proprietary experimental data.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Eye Dam. 1 Skin Irrit. 2 Aquatic Chronic 3	Acute toxicity, category 4 Serious eye damage, category 1 Skin irritation, category 2 Hazardous to the aquatic environment, chronic toxicity, category 3
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road

ATE: Acute Toxicity Estimate

ZUN	FILA INDUSTRIA CHIMICA S.P.A.	Revision nr. 1
FIR		
		Dated 17/03/2022
	PORCELAIN CEMENT RESIDDUE REMOVER	Printed on 03/11/2022
		Page n. 12/13
		First Issue
- CAS: Chemical Abstract Service Num	nber	
- CE50: Effective concentration (require	ed to induce a 50% effect)	
 CE: Identifier in ESIS (European arch 	nive of existing substances)	
- CLP: Regulation (EC) 1272/2008		
- DNEL: Derived No Effect Level		
- EmS: Emergency Schedule	f classification and labeling of chemicals	
	rt Association Dangerous Goods Regulation	
- IC50: Immobilization Concentration 5		
 IMDG: International Maritime Code for 		
- IMO: International Maritime Organiza	tion	
- INDEX: Identifier in Annex VI of CLP		
- LC50: Lethal Concentration 50% - LD50: Lethal dose 50%		
- OEL: Occupational Exposure Level		
- PBT: Persistent bioaccumulative and	toxic as REACH Regulation	
- PEC: Predicted environmental Conce	5	
- PEL: Predicted exposure level		
- PNEC: Predicted no effect concentrat	tion	
- REACH: Regulation (EC) 1907/2006	actional transport of dongorous goods by train	
- TLV: Threshold Limit Value	national transport of dangerous goods by train	
	ould not be exceeded during any time of occupational exposure.	
- TWA: Time-weighted average exposu		
- TWA STEL: Short-term exposure limi		
- VOC: Volatile organic Compounds		
- vPvB: Very Persistent and very Bioac		
- WGK: Water hazard classes (German	n).	
GENERAL BIBLIOGRAPHY		
1. Regulation (EC) 1907/2006 (REACH	H) of the European Parliament	
2. Regulation (EC) 1272/2008 (CLP) of		
3. Regulation (EU) 2020/878 (II Annex		
4. Regulation (EC) 790/2009 (I Atp. CL		
5. Regulation (EU) 286/2011 (II Atp. Cl 6. Regulation (EU) 618/2012 (III Atp. C		
7. Regulation (EU) 487/2013 (IV Atp. C		
8. Regulation (EU) 944/2013 (V Atp. C		
9. Regulation (EU) 605/2014 (VI Atp. C		
10. Regulation (EU) 2015/1221 (VII At		
11. Regulation (EU) 2016/918 (VIII Atp		
12. Regulation (EU) 2016/1179 (IX Atp		
13. Regulation (EU) 2017/776 (X Atp. (14. Regulation (EU) 2018/669 (XI Atp.		
15. Regulation (EU) 2019/521 (XII Atp.		
16. Delegated Regulation (UE) 2018/1-		
17. Regulation (EU) 2019/1148		
18. Delegated Regulation (UE) 2020/2		
19. Delegated Regulation (UE) 2020/1		
20. Delegated Regulation (UE) 2021/6		
21. Delegated Regulation (UE) 2021/8 - The Merck Index 10th Edition	49 (AVII AIP. OLF)	
- Handling Chemical Safety		
- INRS - Fiche Toxicologique (toxicolog	gical sheet)	
- Patty - Industrial Hygiene and Toxico		
- N.I. Sax - Dangerous properties of Ind		
- IFA GESTIS website		
- ECHA website	Niniotry of Loolth and ICC (latitude Conscience of Court(2)). Holy	
- Database of SDS models for chemica	als - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy	
Note for the user:		
	et is based on the knowledge available to us at the date of the latest version	1. The user must ensure the suitability
	n relation to the specific use of the product.	

FILA INDUSTRIA CHIMICA S.P.A.	Revision nr. 1
	Dated 17/03/2022
PORCELAIN CEMENT RESIDDUE REMOVER	Printed on 03/11/2022

Page n. 13/13 First Issue

This document should not be construed as a guarantee of any specific property of the product.

Since the use of the product does not fall under our direct control, it is the user's obligation to observe the laws and regulations in force regarding hygiene and safety under his own responsibility. No responsibility is assumed for improper use. Provide adequate training to personnel assigned to the use of chemical products. This safety data sheet has been prepared by a competent technician who has received suitable training.

METHODS OF CALCULATING THE CLASSIFICATION Physico-chemical hazards: The classification of the product was derived from the criteria established by the CLP Regulation Annex I Part 2. The methods for assessing the physico-chemical properties are reported in section 9.

Health hazards: The classification of the product is based on the calculation methods set out in Annex I of CLP Part 3, unless otherwise indicated in section 11.

Environmental hazards: The classification of the product is based on the calculation methods set out in Annex I of CLP Part 4, unless otherwise indicated in section 12.

First Issue