

## GARAGE PROTECTOR

## CONCRETE



### WHAT IT'S FOR

- Prevents dust formation and dirt absorption.
- Generates a polished film that is also resistant to movements of fork-lift trucks and carts.
- For interior floors.

### ADVANTAGES

- No need to dust and no staining.
- Facilitates maintenance.
- Prolongs floor life.
- Is ideal for industrial plants, warehouses, exhibition halls, garages...
- It is ready to use and should not be diluted.
- Ideal for garages.
- An A+ classified product in accordance with the French VOC regulation



### COVERAGE

With one litre:

**Concrete** **20/25 m<sup>2</sup>**

"Coverage shown is for guidance purposes only and refers to single coats"

### Packaging

5 litres: boxes of 4.

#### WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Protect can from frost.

#### TEMPERATURES

Storage temperature: from 5° to 30° C.  
This product must be applied to surfaces with temperature between 10°C and 30°C.

### HOW TO USE IT

**No dilution required:** ready to use.

#### Application:

1. Wash the floor carefully. Rinse and leave to dry.
2. Apply **BETON** evenly using a brush, roller or wax applicator.
3. Wait 4 hours, then apply a second coat at right angles to the first.

**Maintenance:** diluted solution of **CLEANER PRO**.

#### Caution:

On some concrete floor surfaces **BETON** may not adhere efficiently, so we always recommend conducting a preliminary test.