



ECO-FRIENDLY LIQUID WAX

MARBLE, TERRAZZO, TERRAZZO, NATURAL STONE, TERRACOTTA, CONCRETE TILES



WHAT IT'S FOR

- Protects floors in marble, travertine, and stone agglomerates including terrazzo.
- Revitalises the shine of polished finishes.
- An ideal first and final coat for the traditional treatment of terracotta and for routine maintenance.

ADVANTAGES

- Provides a splendid natural shine.
- Easy to apply and maintain.
- Protects surfaces from the effects of time.
- Does not degenerate with maintenance.
- Can be re-polished to enhance the shine.

CLASSIC is a natural liquid wax that protects and nourishes surfaces enhancing their sheen.



COVERAGE

With one litre:

Terracotta 30 m²

Stone 30/40 m²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1 litre: boxes of 12.

5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Not recommended for use on outdoor surfaces or in damp environments and where water remains (bathrooms, showers).
- The product can change the appearance of the material, first spot test a small area to check for any changes.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

HOW TO USE IT

Dilution: either undiluted or diluted according to requirements.

Protects paving made with marble, agglomerates (Venetian paving, grit), concrete tiles and stone with polished finish:

Existing floors: apply the undiluted wax with a fleece pad or other applicator. Leave to dry thoroughly (about 30 minutes) then buff the surface with a steel-wool pad.

New floors: apply the undiluted or diluted wax evenly with a fleece pad. Leave to dry (about 30 minutes) then buff the surface with a woollen cloth or floor polisher.

For maintenance:

Restoring sheen (every 2-3 months): after having cleaned the surface with a diluted solution of **CLEANER PRO** (1:200), apply **CLASSIC** by diluting 100-200 ml of product in 5 litres of water. Buff the surface once it has dried (after about 30 minutes).

Restoring protection (once a year): apply undiluted wax with a cloth, fleece pad or other applicator. Buff the surface when it is dry (after about 1 hour).