

CONCRETE SHIELD



**WATER-BASED
TECHNOLOGY**

COLOUR-ENHANCING STAINPROOFING PROTECTOR FOR CONCRETE

**CONCRETE, STAMPED CONCRETE,
INTERLOCKING PAVERS, MARBLE CHIP CEMENT
TILE**



Prevents the formation of dust, stops dirt absorption and facilitates cleaning of floors made of concrete, stamped concrete, self-locking paving blocks and marble-chip tiles.



COVERAGE

COVERAGE (1 litre):

10-15 m²

Coverage shown is indicative and refers to single coats.

Packaging

5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- The product is sensitive to frost: store it as indicated on the label.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

WHAT IT'S FOR

- Enhances indoor and outdoor concrete surfaces and protects them against stains and water
- Creates a barrier that facilitates the removal of oil and grease before they penetrate the surface
- When applied outdoors on interlocking pavers, marble-chip tiles and stamped concrete, it makes surfaces resistant to weathering
- Strengthens industrial floors in warehouses, showrooms and garages and makes them dust resistant
- When applied on residential flooring, the treatment may be completed with a wax finish

ADVANTAGES

- **Eco-friendly:** does not contain hydrocarbon solvents
- Reversible treatment
- Consolidating and dust-resistant action
- UV resistant (ASTM G154)
- **Water-based:** not affected by residual moisture, hence drastically reducing on-site work time
- An **A+** classified product in accordance with the French VOC regulation

HOW TO USE IT

No dilution required: ready to use.

Application:

Shake before use. On a clean and dry surface, apply **CONCRETE SHIELD** uniformly using a flat paintbrush, fleece or roller. Once the first coat has dried (after 4 hours), in case of absorbent surfaces, apply a second coat of the product in the same manner.

For indoor domestic environments: 4 hours after the application of **CONCRETE SHIELD**, apply one coat of finishing wax to obtain the desired effect: **MATT** for a natural effect and **LONGLIFE** for a polished effect, if available for sale.

For exteriors: the product should be applied annually to maintain the surface colour enhancement in optimal condition.

For ordinary maintenance: use a diluted solution of **CLEANER PRO** (1:200)

CLEANING OF TOOLS: clean with water after use.

Caution:

*If the product is applied incorrectly or the surface protection must be entirely restored, remove **CONCRETE SHIELD** with **PS87 PRO**. On indoor residential flooring (micro concrete, quartz concrete, etc.), test the product on small inconspicuous area to check the product's compatibility with the surface before treatment. On smooth or polished concrete, **CONCRETE SHIELD** may not adhere correctly. Hence, we recommend testing the product before full application. Do not apply the product outdoors if rain is in forecast. Not recommended for application on external surfaces, in damp environments and wherever water tends to stagnate (showers, saunas, Turkish baths, etc.). If the product is applied on groutless installations, the protection refers exclusively to the top surface of the tile. Since there are so many different materials, before applying the product we recommend testing it on a small area of the surface to check for any colour changes. For regular and heavy-duty cleaning and maintenance, do not use alkaline degreasing cleaners. Use only **CLEANER PRO** neutral cleaner.*