



STONE & GROUT SEALER



CONTRACTOR'S CHOICE

NATURAL STONE, CEMENT GROUT, CONCRETE, TERRACOTTA



WHAT IT'S FOR

- Protects natural stone, grout joints, concrete and terracotta from stains.
- Protects grout joints from water and humidity.
- Makes cleaning fast and easy.
- Keeps grout joints looking new for years.
- Can be used both indoors and outdoors.

ADVANTAGES

- Eco-friendly: water-based.
- Dual-action: protects grout joints and makes cleaning easier.
- Does not alter grout joint color.
- Odorless.
- Fast drying.
- VOC free
- PFOA free: non carcinogenic.

HOW TO USE IT

READY TO USE, no dilution necessary. Allow new grout installations to cure prior to application. The product may be applied to damp surfaces after standing water has been removed. On a clean, dry surface, apply **CONTRACTOR'S CHOICE** with a paint pad, paintbrush, or lambswool applicator, making sure to fully saturate the surface. Let sit for 10 to 15 minutes, keeping the surface wet with sealer without allowing the sealer to dry on the surface. Then, wipe and rub the surface to allow the product to completely penetrate and remove any excess with a dry cloth, applicator pad, microfiber cloth, lambswool pad or sponge. If a second coat is needed, apply it immediately, keeping the surface wet with sealer without allowing the sealer to dry on the surface. The surface may be used for normal foot traffic after 4 hours. Full cure and maximum sealer protection is achieved in 8 hours.

Caution: When sealing grout with ceramic tile, make sure to remove the sealer from the tile with a cloth. The product does not protect against acid stains.

Storage temperature: Between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 50°F and 86°F (10°C and 30°C).

- ▶ **NATURAL LOOK STAIN PROTECTION**
- ▶ **EFFECTIVE AS A GROUT RELEASE**
- ▶ **INDOORS AND OUTDOORS**
- ▶ **MULTIPURPOSE SEALER**
- ▶ **WORKING PROPERTIES:**
- ▶ **SURFACE TRAFFIC = 4 HOURS**
- ▶ **FULL CURE = 8 HOURS**



Coverage:

1 GAL (3.78 L)

Natural stone >

1,400 sq. ft. (130 m²)

Cement grout joints >

Min coverage:

4,000 sq. ft. (372 m²)

Max coverage:

8,000 sq. ft. (743 m²)

Coverage rates are indicative and per coat.



Packaging:

1 GAL (3.78 L) 4 plastic bottles per box

Data sheets are subject to change without notice. Revision date: 2024/04/18 - REV. 02

Fila Chemicals USA, Corp.
 Miami, FL 33172
 tel +1-305-513-0708
 filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over
200 INTERNATIONAL TOP BRANDS
 manufacturers of materials for floors and wall coverings

filasolutions.com