



# CEMENT GROUT HAZE REMOVER



## DETERDEK

PORCELAIN AND CERAMIC TILE, ACID RESISTANT STONE, QUARRY TILE, TERRACOTTA



### WHAT IT'S FOR

- Eliminates cement grout haze, efflorescence, lime deposits and hard water stains.
- Removes soap scum, rust stains, paint and construction dirt.
- Use indoors and outdoors on floors, walls, shower stalls, bathroom fixtures and facades.
- Safe on acid resistant stone, porcelain, ceramic tile and terracotta.
- Ideal for post-installation cleaning: it removes inorganic construction dirt.

### ADVANTAGES

- Concentrated formula: high coverage.
- Eco-friendly: does not emit fumes that are harmful to people or the environment. A welcome alternative to muriatic acid.
- Does not alter the color of the material.
- Does not damage or corrode aluminum and steel trims when used according to the application instructions.
- Can be used as a cleaner or limescale remover, based on the dilution.
- Contains biodegradable ingredients.

### HOW TO USE IT

**POST INSTALLATION CLEANING:** Wet the surface and grout joints with water, then use **DETERDEK** diluted 1:5 (1 QT of product in 5 QT of water). Apply the solution to sections of a few square feet at a time. Let sit 5-10 minutes, then rub vigorously with an abrasive pad or large brush. Remove the residue with a cloth or wet vac and rinse with plenty of water. Should any stubborn dirt remain, repeat the application with a more concentrated solution.

**OUTDOOR CLEANING:** On surfaces with outdoor contaminants (smog, dust, etc.), dilute 1:10 (1 QT of product in 2.5 GAL of water). Then follow the application instructions above.

**Caution:** Do not use on acid sensitive stone such as marble, limestone, or travertine. Test the product on a small, inconspicuous area of the surface or loose sample prior to full application.

**Storage temperature:** between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

- ▶ REMOVES CEMENT GROUT HAZE AND CONSTRUCTION DIRT.
- ▶ DISSOLVES EFFLORESCENCE.
- ▶ CLEANS HARD WATER STAINS, RUST AND PAINT STAINS



#### Coverage:

(1 GAL - 3.78 L)

**Porcelain** > Dilution 1:5  
1,615 sq.ft. (150 m<sup>2</sup>)

**Acid resistant natural stone** > 1:5-1:10  
815-1,430 sq.ft. (76-132 m<sup>2</sup>)

**Terracotta** > Dilution 1:5  
410-815 sq.ft. (38-76 m<sup>2</sup>)

*Coverage rates are indicative.*



#### Packaging:

1 GAL (3.78 L) 4 plastic bottles per box

1 QT (946 ml) 6 plastic bottles per box

Data sheets are subject to change without notice. Revision date: 2024/04/18 - REV. 02

Fila Chemicals USA, Corp.  
Miami, FL 33172  
tel +1-305-513-0708  
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over  
**200 INTERNATIONAL TOP BRANDS**  
manufacturers of materials for floors and wall coverings

filasolutions.com