



# EPOXY GROUT HAZE REMOVER

## EPOXYOFF

PORCELAIN AND CERAMIC TILE, GLASS MOSAIC, QUARRY TILE



### WHAT IT'S FOR

- Effectively removes cured epoxy, urethane and pre-mixed grout haze.
- Perfect for nonabsorbent materials: porcelain and ceramic tile, quarry tile, glass mosaic.
- Eliminates organic stains: grease, wine, coffee and other food stains.
- Effective on the toughest ground-in dirt and residue.

### ADVANTAGES

- Gel-like consistency: the formula can be easily applied on vertical surfaces.
- Does not harm surfaces.
- Water-based.
- Pleasant almond scent.
- Contains biodegradable ingredients.
- Interior and exterior use.

### HOW TO USE IT

Wait at least 24 hours after grouting before applying **EPOXYOFF**. Make sure the grout is fully cured. Shake well before use. Apply **EPOXYOFF** directly on the surface with a large, flat paintbrush. Make sure to cover the grout residue and organic stains on horizontal and vertical surfaces. Let sit for 30 minutes. Scrub with an abrasive pad. Use a spatula to remove any remaining residue. Rinse thoroughly. For large surface areas, use a floor scrubbing machine fitted with the appropriate pad. Rinse thoroughly. To remove stubborn residue, repeat the application instructions above and increase the dwell time.

**Caution:** Test the product and dwell times on a small, inconspicuous area of the surface or loose sample before full application. Do not use on absorbent materials such as natural stone, wood or plastic (polymethyl methacrylate and similar). Test the product on metal surfaces to verify their resistance before full application.

**Storage temperature:** between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

- ▶ **EFFECTIVELY REMOVES EPOXY, URETHANE & PRE-MIXED GROUT RESIDUE.**
- ▶ **GEL-LIKE CONSISTENCY**

**Coverage:**

1QT (0.95 L)  
up to 108 sq.ft. (10 m<sup>2</sup>)  
*Coverage rates are indicative.*

**Packaging:**

1 QT (946 ml) 6 plastic bottles per box

Data sheets are subject to change without notice. Revision date: 2024/07/30 - REV. 04

**Fila Chemicals USA, Corp.**  
Miami, FL 33172  
tel +1-305-513-0708  
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over  
**200 INTERNATIONAL TOP BRANDS**  
manufacturers of materials for floors and wall coverings

filasolutions.com