



# ULTIMATE POROUS STONE SEALER

## FOB

ALL POROUS NATURAL STONE, GROUT, CONCRETE, QUARRY TILE, TERRACOTTA

## ADVANCED SOLVENT TECHNOLOGY



### WHAT IT'S FOR

- Natural look, penetrating sealer that protects all porous natural stone, grout, concrete, quarry tile and terracotta against stains.
- Forms an invisible, protective barrier resistant to moisture and stains while allowing water vapor to escape.
- Suitable for indoor and outdoor surfaces.
- Ideal for the treatment of concrete and quarry tile.
- Perfect for honed marble, limestone and travertine.
- Ideal for use in kitchens, under barbecues, on driveways and in high traffic areas both indoors and outdoors.

### ADVANTAGES

- Long lasting protection.
- Does not yellow or discolor over time.
- UV resistant.
- Treated surfaces are safe for food contact.
- Does not alter the frost resistance of terracotta.
- PFOA free: non carcinogenic.

### HOW TO USE IT

**READY TO USE**, no dilution necessary.

**Indoor surfaces:** On a dry and clean surface, apply an even coat of **FOB** with a paintbrush, lambswool or roller applicator. Before the product dries, about 10 minutes, wipe and rub the surface to allow any excess product to completely penetrate or be removed. Wait 8 hours to apply a second coat if necessary, following the instructions above. The surface may be used for normal foot traffic 8 hours after the final coat. Full cure and maximum sealer protection is achieved in 24 hours.

**Outdoor surfaces:** On a clean and dry surface, apply two coats of **FOB** with a large paintbrush or roller allowing 8 hours between coats.

**Caution:** Do not apply **FOB** on a previously waxed surface, strip it first. Do not apply **FOB** during the warmest hours of the day in the summer. Before full application, test the product on a small, inconspicuous area of the surface or loose sample to check for any discoloration. Do not apply **FOB** outdoors if rain is in the forecast. The product does not protect surfaces from acid stains.

**Storage temperature:** Between 32°F and 86°F (0°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

- ▶ **NATURAL LOOK**
- ▶ **LONG-LASTING PROTECTION**
- ▶ **INTERIOR AND EXTERIOR USE**
- ▶ **WORKING PROPERTIES:**  
**SURFACE TRAFFIC = 8 HOURS**  
**FULL CURE = 24 HOURS**



#### Coverage:

1 GAL (3.78 L)

**All natural stone >**

430/861 sq. ft. (40-80 m<sup>2</sup>)

**Concrete, quarry tile, terracotta >**

646/861 sq. ft. (60-80 m<sup>2</sup>)

**Grout\* >** 1,400 sq. ft. (130 m<sup>2</sup>)

*Coverage rates are indicative and per coat.*

*\*Grout coverage varies according to tile size, grout joint width and porosity of the grout.*



#### Packaging:

1 QT (946 ml) 6 plastic bottles per box

1 GAL (3.78 L) 4 plastic bottles per box

Data sheets are subject to change without notice. Revision date: 2024/07/30 - REV. 02

Fila Chemicals USA, Corp.  
Miami, FL 33172  
tel +1-305-513-0708  
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over  
**200 INTERNATIONAL TOP BRANDS**  
manufacturers of materials for floors and wall coverings

filasolutions.com