

EXTREME WATER- AND OIL-REPELLENT PROTECTION

NATURAL STONE, AGGLOMERATES, MARBLE AND GRANITE, CONCRETE, TUFF, WPC, TERRACOTTA, QUARRY TILES



FOB XTREME, a water- and oil-repellent breathable protective agent, is based on the innovative **ADVANCED SOLVENT-BASED TECHNOLOGY**, developed in the FILA research laboratories. It does not create a surface film and withstands UV radiation, preserving its performance over time.



COVERAGE

COVERAGE (1 litre):	
Stone	10-30 m ²
Terracotta rustic Tuscan, polished	15-20 m ²
Terracotta handmade	up to 10 m ²
Concrete	up to 5 m ²
Polished Marble/Granite	up to 30 m ²

Coverage shown is indicative and refers to single coats

Packaging

1 litre: boxes of 6.

5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Ventilate the area if applied on interior surfaces.
- The use of a single-disc cleaning machine is permitted only if it is in perfect working condition.
- Outdoor flooring must be properly laid before being treated and must satisfy all specific requirements, including: adequate sloping, properly executed expansion joints, perfect insulation from underlying ground, proven compatibility with sub-zero temperatures.
- Does not protect against acid aggression.

TEMPERATURES

Storage temperature: from 0°C to 30°C

The product should be applied to materials with temperature between 5° and 30°C.

WHAT IT'S FOR

- Water- and oil-repellent: it hampers the absorption of common watery and oily stains
- Protective base coat before waxing internal surfaces with rustic or textured finishes
- Excellent for the treatment of terrazzo and coloured cement tiles
- Natural-finish breathing protection

ADVANTAGES

- Does not alter original colour and appearance
- Does not form surface film
- Does not alter terracotta frost resistance
- Excellent on rustic ground terracotta and tumbled marble
- Ideal for use near kitchens, barbecues and car driveways
- Ideal for interior and exterior surfaces
- Treated surfaces are safe for food contact
- An **A+** classified product in accordance with the French VOC regulation

HOW TO USE IT

No dilution required: ready to use.

Application:

For materials with matt finish (indoors and outdoors): Apply the product evenly and continuously on a clean and dry surface using a brush or fleece pad, wetting the grout lines as well. Dab any excess product with a clean cloth before it dries (roughly 10-15 minutes).

For glossy or brushed finishes (indoors and outdoors): Apply **FOB XTREME** on a clean and dry surface, wetting the material and grout lines completely using a brush or fleece pad. Before the product dries (roughly 10-15 minutes), rub the surface and remove any residues using a microfibre cloth wetted with the product. Dry the surface with a clean cloth. When requested on high-absorption materials, apply two coats of the product with an 8-hour interval in between (e.g.: highly-trafficked areas, humid areas, outdoor surfaces). To speed up the process, it is possible to treat the surface with a single-disc floor scrubber.

To complete the cycle with the finish: on porous materials such as natural stone, reconstructed tiles, agglomerates and concrete tiles laid in indoor environments, a finishing wax can be applied depending on the material and on the desired effect (**MATT** for a natural effect, **SATIN** for a satin effect, **LONGLIFE** or **CLASSIC** for a polished effect, if available for sale). The surface can be walked on after just 8 hours. The stain-proofing effect starts after 24 hours.

For ordinary maintenance: use a diluted solution of **CLEANER PRO** (1:200)

Caution:

*Never apply **FOB XTREME** onto a surface that is already waxed.*

*Do not apply **FOB XTREME** during the hottest hours of the day in summer.*

Since there are so many different materials, before applying the product we recommend testing it on a small area of the surface to check for any colour changes.

Do not apply the product outdoors if rain is in forecast.

Does not protect against acid aggression.