

EXTREME WATER- AND OIL-REPELLENT PROTECTION

NATURAL STONE AND AGGLOMERATES, MARBLE AND GRANITE, CONCRETE, TUFF, WPC, TERRACOTTA, QUARRY TILES



FOB XTREME, a water- and oil-repellent breathable protective agent, is based on the innovative **ADVANCED SOLVENT-BORNE TECHNOLOGY**, developed in the **FILA** research laboratories. It does not create a surface film and withstands UV rays, preserving its performance over time.



COVERAGE

APPROXIMATE COVERAGE (1 litre):

Stone	10/30 m ²
Terracotta rustic Tuscan, polished	15/20 m ²
Terracotta handmade	up to 10 m ²
Concrete	up to 5 m ²
Polished Marble/Granite	up to 30 m ²

“Coverage shown is for guidance purposes only and refers to single coats”

Packaging

1 litre: boxes of 6.

5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Ventilate the area if applied on internal surfaces.
- The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.
- Outdoor flooring must be properly laid before being treated and must satisfy all specific requirements, including: adequate sloping, properly executed expansion joints, perfect insulation from underlying ground, proven compatibility with sub-zero temperatures.
- Does not protect against acidic aggression.

TEMPERATURES

Storage temperature: from 0°C to 30°C

The product should be applied to materials with temperature between 5° and 30°C.

WHAT IT'S FOR

- Water- and oil-repellent: it hampers the absorption of common watery and oily stains.
- Protective base coat before waxing internal surfaces with rustic or textured finishes.
- Excellent for coloured concrete tiles.
- Natural effect breathing protection.

ADVANTAGES

- Does not alter original colour and appearance.
- Does not form surface film
- Does not alter terracotta frost resistance.
- Excellent on rustic ground terracotta and tumbled marble.
- Ideal for use near kitchens, barbecues and car driveways.
- Ideal for interior and exterior surfaces.
- Treated surfaces are safe for food contact
- An **A+** classified product in accordance with the French VOC regulation

HOW TO USE IT

No dilution required: ready to use.

Application:

For materials with matt finish (indoors and outdoors): Apply the product evenly and continuously on a clean and dry surface using a brush or fleece pad, wetting the grout lines as well. Dab any excess product with a clean cloth before it dries (roughly 10-15 minutes).

For glossy or brushed finishes (indoors and outdoors): Apply **FOB XTREME** on a clean and dry surface, wetting the material and grout lines completely using a brush or fleece pad. Before the product dries (roughly 10-15 minutes), rub the surface and remove any residues using a microfibre cloth wetted with the product. Dry the surface with a clean cloth. When requested on high-absorption materials, apply two coats of the product with an 8-hour interval in between (e.g.: highly-trafficked areas, humid areas, outdoor surfaces). To speed up the process, it is possible to treat the surface with a single-disc floor scrubber.

To complete the cycle with the finish: on porous materials such as natural stone, reconstructed tiles, agglomerates and concrete tiles laid in indoor environments, a finishing wax can be applied depending on the material and on the desired effect (**MATT, SATIN, CLASSIC, LONGLIFE**). The surface can be walked on after just 8 hours. The stain-proofing effect starts after 24 hours.

Maintenance: use a diluted solution of **CLEANER PRO**.

Caution:

*Never apply **FOB XTREME** onto a surface that is already waxed.*

*Do not apply **FOB XTREME** during the hottest hours of the day in summer.*

Carry out a patch test on a small surface area to check for any changes in colour.

Do not apply the product externally if rain is forecast.

Does not protect against acidic aggression.