



WATER REPELLENT SEALER

HYDROREP

ALL UNPOLISHED NATURAL STONE, CONCRETE, TERRACOTTA

SOLVENT BASED
TECHNOLOGY



WHAT IT'S FOR

- Protects exterior surfaces and grout joints from water and humidity.
- Creates a water repellent, breathable barrier.
- Prevents wear caused by weather damage.
- Guards the surface against moss, mold and efflorescence.
- Ideal for thin brick and concrete.

ADVANTAGES

- Does not alter the material's natural finish.
- Offers long lasting, renewable protection.
- Provides very high coverage rates.
- Does not yellow over time.
- High penetration.

HOW TO USE IT

READY TO USE, no dilution necessary. On a clean, dry surface apply an even, generous coat of **HYDROREP** with a brush, roller or airless sprayer. Apply the product until the surface is fully saturated, then wait 8 hours. A second coat may be necessary, depending on the absorbency of the material. On dense natural stone apply only one coat. For concrete and porous natural stone, two coats are needed. The surface may be used for normal foot traffic after 8 hours. Full cure and maximum sealer protection is achieved in 24 hours. To provide an oil repellent barrier on exterior surfaces, apply a finishing coat of **FOB** after 8 hours.

Caution: Before application, test **HYDROREP** on a small, inconspicuous area of the surface or loose sample to check for any changes in color. Do not apply the product outdoors if rain is in the forecast. The product does not protect against acid stains.

Storage temperature: Between 32°F and 86°F (0°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

22

- ▶ **PREVENTS MOLD**
- ▶ **CAN BE USED AROUND POOL AREAS**
- ▶ **WORKING PROPERTIES:**
SURFACE TRAFFIC = 8 HOURS
FULL CURE = 24 HOURS



Coverage:

1 Liter (1.06 QT)

Natural stone >

215 sq.ft. (20 m²)

Concrete >

54-107 sq.ft. (5-10 m²)

Coverage rates are indicative and per coat.



Packaging:

1 Liter (1.06 QT) 6 plastic bottles per box

Data sheets are subject to change without notice. Revision date: 2024/07/30 - REV. 03

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over
200 INTERNATIONAL TOP BRANDS
manufacturers of materials for floors and wall coverings

filasolutions.com