

WATER REPELLENT SEALER



HYDROREP

ALL UNPOLISHED NATURAL STONE, CONCRETE

SOLVENT BASED TECHNOLOGY



- NATURAL LOOK FINISH
- LONG LASTING PROTECTION

WHAT IT'S FOR

- Protects exterior surfaces and grout joints from water and humidity.
- Creates a water repellent, breathable barrier.
- Prevents wear caused by weather damage.
- Guards the surface against moss, mold and efflorescence.
- Ideal for brick veneers and concrete.

ADVANTAGES

- Does not alter the material's natural finish.
- Offers long lasting, renewable protection.
- Provides very high coverage rates.
- Does not yellow over time.

HOW TO USE IT

Ready to use, no dilution necessary.

On a clean, dry surface apply an even, generous coat of **HYDROREP** with a brush, roller or airless sprayer. Apply the product until the surface is fully saturated, then wait 8 hours. A second coat may be necessary, depending on the absorbcency of the material. On dense natural stone apply only one coat. For concrete and porous natural stone, two coats are needed. To provide an oil repellent barrier on exterior surfaces, apply a finishing coat of **FOB** after 8 hours.

Caution: Before application, test **HYDROREP** on a small, inconspicuous area of the surface or loose sample to check for any changes in color. Do not apply the product outdoors if rain is in the forecast.



Coverage:

1 Liter (1.06 QT)

Natural stone ▶ 215 sq.ft. (20 m²)

Concrete ▶ 54-107 sq.ft. (5-10 m²)

Coverage rates are indicative and per coat.



Packaging:

1 Liter (1.06 QT) 12 cans per box