CEMENT GROUT REMOVER

INSTANT REMOVER

PORCELAIN AND CERAMIC TILE, GLASS MOSAIC, QUARRY TILE





REMOVES GROUT RESIDUE BEFORE IT CURES, PREVENTING GROUT HAZE SPEEDS UP GROUT CLEANUP TIME DRIES FAST



up to 161 sq.ft. (15 m²) Large format tile grout joints > up to 1,148 linear feet (350 linear meters) Mosaic > up to 161 sq.ft. (15 m²) Coverage rates are indicative.



WHAT IT'S FOR

- Eliminates fresh cement grout residue during installation, before it cures.
- Effective on grout with additives.
- Ideal for cleaning the back of large format tile prior to installation.
- Perfect for cleaning grouting tools.

ADVANTAGES

- RAPIDDRY TECHNOLOGY: dries quickly, to be used during installation.
- No foam.
- Does not damage grout joints.
- Does not damage or corrode aluminum and steel trims.
- Use indoors and outdoors, ideal for floors and vertical surfaces.
- High coverage.
- Safe for the installer and the environment: does not emit harmful fumes.
- Patented: application system with effective and certified results.

HOW TO USE IT

READY TO USE. Wait for the grout to initially set and become firm to the touch (usually about 10 to 30 minutes, according to the grout manufacturer's instructions). Carry out an initial cleaning of the surface with a damp sponge. Then, spray **INSTANT REMOVER** and let sit for 1-2 minutes. For textured tile, let sit for 5-10 minutes. Clean using a sponge trowel, rinsing it often to keep it clean. For stubborn stains, repeat the above instructions after one hour. Refer to the grout manufacturer's instructions for indications about when the surface is safe to use. To clean the back of large format tile: Spray **INSTANT REMOVER** on a soft sponge and wipe the back of the tile.

Caution: Do not use on acid sensitive materials. Do not use abrasive sponges. Test the product before use to determine the material's resistance and the dwell time required for the product to reach maximum effectiveness.

Storage temperature: between 41° F and 86° F (5° C and 30° C). Must be applied at temperatures between 41° F and 86° F (5° C and 30° C).

Data sheets are subject to change without notice. Revision date: 2024/07/30 - REV. 03

Fila Chemicals USA, Corp. Miami, FL 33172 tel +1-305-513-0708 filausa@filasolutions.com

TOLL FREE 1-844-FILA123





Recommended by over **200 INTERNATIONAL TOP BRANDS** manufacturers of materials for floors and wall coverings filasolutions.com

