



GLOSSY PROTECTIVE WAX

TERRACOTTA, QUARRY TILES, SLATE, STONE AND AGGLOMERATES, RUBBER AND PVC, LAMINATE FLOORING, LINOLEUM, RESIN, VINYL SURFACES



WHAT IT'S FOR

- Protects floors subjected to high traffic.
- Perfect for flooring made from rubber, PVC, vinyl, plastic laminates, linoleum and resin.
- Ideal for protecting unpolished natural stone, granite and terracotta floors.
- Excellent also for maintaining quartz concrete floors treated with **BETON**.
- Generates a high-gloss and ultra-protective polymer surface film.
- Ideal for protecting polished natural stone floors in public areas.

ADVANTAGES

- No need to polish.
- High adhesion capacity.
- Easy application.
- Can be undiluted or diluted as necessary.
- Maintenance can be carried out using a single-disc cleaning machine at high speed.
- Non-drip finish (ISO 10545-17 standard, Annex A, B.C.R.A. method)



COVERAGE

With one litre:	
Terracotta	30 m ²
Stone	30/40 m ²
Rubber/PVC, plastic laminates, Linoleum, Resin (undiluted)	30 m ²
Rubber/PVC, plastic laminates, Linoleum, Resin (diluted 1:10)	300 m ²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1 litre: boxes of 12.
5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

HOW TO USE IT

For protecting surfaces: Apply one coat of the product evenly and continuously on a clean and dry floor, using a fleece pad or other applicator. Wait 1 hour. Then apply a second coat at right angles to the first. When dry, the floor will shine without requiring polishing. When treating highly absorbent terracotta and natural stone surfaces, we recommend first applying a base coat of **FOB XTREME** or **W68**. Wait 24 hours before applying **LOGLIFE**.

For maintenance:

Restoring sheen (every 2-3 months): after cleaning the surface with a diluted solution of **CLEANER PRO** (1:200), apply **LOGLIFE** diluting 500 ml of product in 5 litres of water. The floor can be walked on once it is dry.

To restore the protection (once a year): dewax the surface using **PS87 PRO** detergent diluted 1:5. Rinse. Apply **LOGLIFE** undiluted on the dry and clean floor using fleece or other applicator. The floor can be walked on once dry.

Caution:

Do not walk on floor while it's drying and do not repeat application on treated areas which are not yet dry.

*To remove this wax, use the specific wax-remover **PS87 PRO**.*

Not recommended for use on outdoor surfaces or in damp environments and where water remains (bathrooms, showers).

The product can change the appearance of the material, first spot test a small area to check for any changes.