

# MATTE FINISH PROTECTIVE WAX

## MATT

UNPOLISHED NATURAL STONE, QUARRY TILE, TERRACOTTA



- PROVIDES THE SURFACE WITH A DURABLE, LOW SHEEN, NATURAL FINISH.
- PROTECTS PLASTERED AND ENGINEERED STONE WALLS.



**Coverage:**

1 Liter (1.06 QT)

**Quarry tile, terracotta** > 325 sq. ft. (30 m<sup>2</sup>),  
**Unpolished natural stone** > 215/535 sq. ft. (20-50 m<sup>2</sup>)  
*Coverage rates are indicative and per coat.*



**Packaging:**

1 Liter (1.06 QT) 12 plastic bottles per box

### WHAT IT'S FOR

- Maintains unpolished natural stone, quarry tile and terracotta.
- Gives the surface a durable, low sheen, natural finish.
- Ideal finishing coat over a water-based or solvent-based sealer.
- Prevents dust from settling and staining natural stone and terracotta.
- For a sating finish, simply polish the treated surface.

### ADVANTAGES

- Easy to remove.
- Highly concentrated – can be diluted according to use.
- Essentially self-leveling due to its consistency.

### HOW TO USE IT

Do not use **MATT** on outdoor surfaces.

**Surface protection:** apply one coat of the product with a clean cloth or lambswool applicator. Wait until the surface is completely dry (about 1-2 hours), then apply a second coat perpendicular to the first. Do not walk on the floor for an hour after the second application. Surfaces treated with **MATT** can be buffed with a wool cloth or floor polishing machine for a shinier finish.

**Surface maintenance:** Dilute 1:10 (two capfuls per gallon of water), then wipe the floor with a long handled brush or cloth.

**Caution:** Wax application is not recommended on outdoor surfaces, in wet environments or any place with standing water. **MATT** can be removed with **PS87**.