




IMPREGNATING SEALER



MP90

ALL NATURAL STONE, QUARTZ, POLISHED PORCELAIN, GROUT

SOLVENT TECHNOLOGY



WHAT IT'S FOR

- Effectively seals and protects all stone and polished porcelain tile against stains.
- Ideal protection for polished kitchen countertops and bathroom vanities.
- Perfect for tables and windowsills.
- Suitable for the protection of crackle tile.
- Makes everyday maintenance easy.

ADVANTAGES

- Does not form a film or discolor over time.
- Treated surfaces are safe for food contact.
- Does not alter the natural look of the surface.
- PFOA free: non carcinogenic.
- Provides anti-graffiti protection.

HOW TO USE IT

READY TO USE, no dilution necessary. On a clean, dry surface, apply **MP90** with a paint pad, paintbrush, or lambswool applicator, making sure to fully saturate the surface. Let sit for 10 to 15 minutes, keeping the surface wet with sealer without allowing the sealer to dry on the surface. Then, wipe and rub the surface to allow the product to completely penetrate and remove any excess with a dry cloth, applicator pad, microfiber cloth, lambswool pad or sponge. If a second coat is needed, apply it immediately, keeping the surface wet with sealer without allowing the sealer to dry on the surface. The sealer may be used for normal foot traffic after 8 hours. Full cure and maximum sealer protection is achieved in 24 hours. For very porous surfaces, use **FOB**.

Caution: Before full application, test the product on a small, inconspicuous area of the surface (especially on highly absorbent materials) or loose sample to check for any discoloration. Apply and leave the product to dry in a well ventilated area. Do not apply the product outdoors if rain is in the forecast. **MP90** does not protect surfaces against acids stains.

Storage temperature: Between 32°F and 86°F (0°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

- ▶ **NATURAL LOOK**
- ▶ **DEEP PENETRATION**
- ▶ **INTERIOR AND EXTERIOR USE**
- ▶ **WORKING PROPERTIES:**
SURFACE TRAFFIC = 8 HOURS
FULL CURE = 24 HOURS



Coverage:

- 1 GAL (3.78 L)
- Polished stone** >
1200 sq.ft. (112 m²)
- Polished porcelain tile** >
1200-1600 sq.ft. (112-149 m²)
- Unpolished natural stone** >
400-800 sq.ft. (36-76 m²)
- Quartz** >
1,600 sq.ft. (149 m²)
- Grout** >
1,400 sq. ft. (130 m²)

Coverage rates are indicative and per coat.



Packaging:

- 1 GAL (3.78 L): 4 plastic bottles per box
- 1 QT (946 ml) 6 plastic bottles per box
- 1 PT (473 ml) 12 plastic bottles per box

Data sheets are subject to change without notice. Revision date: 2024/04/18 - REV. 02

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over
200 INTERNATIONAL TOP BRANDS
manufacturers of materials for floors and wall coverings

filasolutions.com