

WATER- AND OIL-REPELLENT PROTECTION

POLISHED PORCELAIN TILES, MARBLE, GRANITE, NATURAL STONE, AGGLOMERATES



MP90, a breathable oil- and water-repellent protective agent, prevents the absorption of oily or greasy substances (oil, soap, shampoo, etc.) and water on surfaces, preserving their original appearance.



COVERAGE

COVERAGE (1 litre):

Marble/Granite	30 m ²
porcelain tiles	30-40 m ²
Venetian terrazzo	30 m ²

Coverage shown is indicative and refers to single coats

Packaging

1 litre: boxes of 6.

5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Ventilate the premises well during application and while the product is drying.
- Does not protect against acid aggression.
- The use of a single-disc cleaning machine is permitted only if it is in perfect working condition.

TEMPERATURES

Storage temperature: from 0° to 30°C.

The product should be applied to materials with temperature between 5° and 30°C.

WHAT IT'S FOR

- The best stain-proofing product for porcelain tiles, marble and granite
- It offers an anti-graffiti treatment for vertical natural stone surfaces
- It is ideally suited for protecting kitchen and bathroom tops
- Stain-proofing: it hampers the absorption of common watery and oily stains

ADVANTAGES

- Does not change the natural colour of surfaces
- Does not form surface film
- Treated surfaces are safe for food contact
- Impregnates, protects, and makes cleaning easier
- It waterproofs, protects and facilitates cleaning
- Ideal for the protection of crackle glazed tiles
- An **A+** classified product in accordance with the French VOC regulation

HOW TO USE IT

No dilution required: ready to use.

Application: apply **MP90** evenly and continuously on a clean and dry surface using a brush, wetting the grout lines as well. Before the product dries completely (after roughly 10–15 minutes), rub the surface and remove any residues using a microfibre cloth wetted with the product. Dry the surface with a clean cloth. To speed up the process, it is possible to treat the surface with a single-disc machine.

On highly absorbent materials, apply two coats of the product with an 8-hour interval in between. The surface can be walked on after 12 hours while the water- and oil-repellent protection becomes effective after 24 hours.

For ordinary maintenance: use a diluted solution of **CLEANER PRO** (1:200)

Caution:

Since there are so many different materials, before applying the product we recommend testing it on a small area of the surface to check for any colour changes. Do not apply the product outdoors if rain is in forecast. Does not protect against acid aggression.