

# MP90 ECO XTREME

## EXTREME ECO-COMPATIBLE WATER- AND OIL-REPELLENT PROTECTION



Thanks to the innovative **ULTIMATE SHIELD TECHNOLOGY**, developed in the **FILA** research laboratories, the product can be applied in the presence of residual humidity, a mere 24 hours after the initial wash.



### COVERAGE

#### COVERAGE (1 litre):

|                          |                      |
|--------------------------|----------------------|
| Polished porcelain tiles | 30-50 m <sup>2</sup> |
| Polished Marble/Granite  | 20-30 m <sup>2</sup> |
| Matte polished stone     | 10-20 m <sup>2</sup> |

Coverage shown is indicative and refers to single coats

#### Packaging

375 mL: boxes of 12.  
1 litre: boxes of 6.  
5 litres: boxes of 4.

#### WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Outdoor flooring must be properly laid before being treated and must satisfy all the specific requirements, including: adequate sloping, properly executed expansion joints, perfect isolation from the underlying ground, proven compatibility with sub-zero temperatures.
- Ventilate the premises well during application and while the product is drying.
- Does not protect against acid aggression.

#### TEMPERATURES

Storage temperature: from 5° to 30° C.  
This product must be applied to surfaces with temperature between 10°C and 30°C.

**POLISHED PORCELAIN TILES, MARBLE, GRANITE,  
NATURAL STONE, AGGLOMERATES, CONCRETE**

### WHAT IT'S FOR

- Water- and oil-repellent with natural finish
- The best environmentally-friendly stain protection for porcelain tiles, natural stone, marble and granite with polished, brushed and matt smoothed finishes
- Reduces absorption without affecting the material's natural look
- It waterproofs, protects and facilitates cleaning
- It is also ideal for grouting joints, ceramic and crackle effect surfaces, terrazzo, resin-marble, and stone slabs
- Is also suitable for treating coloured cement tiles and manufactured stones
- It provides an anti-graffiti protection that prevents graffiti paint from bonding to surfaces. It speeds the cleaning process because graffiti can be easily removed
- Water- and oil-repellent: it hampers the absorption of common watery and oily stains

### ADVANTAGES

- A product with an extremely low VOC and a low eco-impact that also has the **INDOOR AIR COMFORT GOLD** certificate \*
- Free of hydrocarbon solvents: eco-friendly treatment
- Being a water-based product, it withstands residual humidity conditions and can therefore be applied 24-48 hours after the initial wash, thus speeding up the treatment
- An A+ classified product in accordance with the French VOC regulation
- A product certified according to EMICODE EC1 Plus and LEED (ACP)
- Does not form surface film and does not yellow
- Ideal for protecting tables, as well as kitchen and bathroom tops
- The surface can be walked on after just 2 hours\*\*

#### \*\*Application conditions:

temperature = 20°C

humidity < or = 60%

Apply according to the indications shown on the label

\* The product has passed the applicable stringent requirements and conforms to all compulsory national standards (for example: French A+, CAM Edilizia, Belgian Regulation, AgBB, etc.) as well as innovative environmental sustainability criteria, such as LEED, BREEAM, WELL. For further information consult <https://www.filasolutions.com/eng/company/the-fila-research-centre>

### HOW TO USE IT

**No dilution required:** ready to use.

**Application:** Shake before use.

**For materials with matt finish (natural stone, terracotta, agglomerates, concrete tiles):** Apply **MP90 ECO XTREME** evenly and continuously on a clean and dry surface using a brush or fleece pad, wetting the grout lines as well.

Dab any excess product with a clean cloth before it dries. On highly absorbent materials, apply two coats of product with a 20-minute interval in between.

**For polished porcelain tiles, natural stone, agglomerates with glossy finish:**

Apply **MP90 ECO XTREME** on a clean and dry surface, wetting the material and grout lines completely using a brush or fleece pad. Before the product dries (roughly 10-15 minutes), rub it using a microfibre cloth wetted with the product to favour its penetration. Dry the surface with a clean cloth. To speed up the process, it is possible to treat the surface with a single-disc machine.

**To complete the cycle with the finish:** On porous materials such as natural stone, reconstructed tiles, agglomerates and cement tiles laid in indoor environments, a finishing wax can be applied depending on the material and on the desired effect (**MATT, SATIN, CLASSIC, LONGLIFE**, if available for sale) after 4 hours. The surface can be walked on after just 2 hours. Water- and oil-repellent protection takes effect after 24 hours.

**CLEANING OF TOOLS:** clean with water after use.

**For ordinary maintenance:** use a diluted solution of **CLEANER PRO** (1:200)

#### Caution:

Since there are so many different materials, before applying the product we recommend testing it on a small area of the surface to check for any colour changes. Do not apply the product outdoors if rain is in forecast.  
Does not protect against acid aggression.