

MP90 ECO XTREME



EXTREME ECO-COMPATIBLE WATER- AND OIL-REPELLENT PROTECTION

**POLISHED PORCELAIN TILES, MARBLE
AND GRANITE, NATURAL STONE AND
AGGLOMERATES, CONCRETE**



Thanks to the innovative **ULTIMATE SHIELD TECHNOLOGY**, developed in the **FILA** research laboratories, the product can be applied in the presence of residual humidity, a mere 24 hours after the initial wash.



COVERAGE

APPROXIMATE COVERAGE (1 litre):

polished porcelain tiles	30-50 m ²
Polished Marble/Granite	20-30 m ²
Matte honed stone	10-20 m ²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

375 ml: boxes of 12.
1 litre: boxes of 6.
5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Outdoor flooring must be properly laid before being treated and must satisfy all the specific requirements, including: adequate sloping, properly executed expansion joints, perfect isolation from the underlying ground, proven compatibility with sub-zero temperatures.
- Ventilate the premises well during use and while the product is drying.
- Does not protect against acidic aggression.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10° C and 30° C.

WHAT IT'S FOR

- Water- and oil-repellent with natural finish.
- The best environmentally-friendly stain protection for porcelain tiles, natural stone, marble and granite with polished, brushed and matt smoothed finishes.
- Reduces absorption without affecting the material's natural look.
- It waterproofs, protects and facilitates cleaning.
- It is also ideal for grouting joints, ceramic and crackle effect surfaces, grit, resin-marble, and stone slabs.
- Is also suitable for treating coloured cement tiles and manufactured stones.
- It provides an anti-graffiti protection that prevents graffiti paint from bonding to surfaces. It speeds the cleaning process because graffiti can be easily removed.
- Water- and oil-repellent: it hampers the absorption of common watery and oily stains.

ADVANTAGES

- Free of hydrocarbon solvents: eco-friendly treatment
- Being a water-based product, it withstands residual humidity conditions and can therefore be applied 24–48 hours after the initial wash, thus speeding up the treatment
- Single-coat application: apply the product and rub it gently over the surface until it is completely absorbed
- Does not form surface film and does not yellow
- Ideal for protecting tables, as well as kitchen and bathroom tops
- The surface can be walked on after just 2 hours**.
- A product with an extremely low VOC and a low environmental impact; it also has the INDOOR AIR COMFORT GOLD certificate*

**Application conditions: temperature = 20°C • humidity < or = 60%
Apply according to the indications shown on the label.

* A product with an extremely low VOC and a low environmental impact; it also has the INDOOR AIR COMFORT GOLD certificate. The product has passed the applicable stringent requirements and conforms to all compulsory national standards (for example: FrenchA+, CAM Edilizia, Belgian Regulation, AgBB, etc.) as well as innovative environmental sustainability criteria, such as LEED, BREEAM, WELL. For further information consult www.filasolutions.com/ita/azienda/ricerca-e-sviluppo

HOW TO USE IT

No dilution required: ready to use.

Application:

Shake before use. For materials with matt finish (natural stone, terracotta, agglomerates, concrete tiles): Apply **MP90 ECO XTREME** evenly and continuously on a clean and dry surface using a brush or fleece pad, wetting the grout lines as well. Dab any excess product with a clean cloth before it dries. On highly absorbent materials, apply two coats of product with a 20-minute interval in between.

For polished porcelain tiles, natural stone, agglomerates with glossy finish: Apply **MP90 ECO XTREME** on a clean and dry surface, wetting the material and grout lines completely using a brush or fleece pad. Before the product dries (roughly 10-15 minutes), rub it using a microfibre cloth wetted with the product to favour its penetration. Dry the surface with a clean cloth. To speed up the process, it is possible to treat the surface with a single-disc floor scrubber.

To complete the cycle with the finish: On porous materials such as natural stone, reconstructed tiles, agglomerates and concrete tiles laid in indoor environments, a finishing wax can be applied depending on the material and on the desired effect (**MATT, SATIN, CLASSIC, LONGLIFE**). The surface can be walked on after just 2 hours. Water- and oil-repellent protection takes effect after 24 hours.

Maintenance: use a diluted solution of **CLEANER PRO**.

Caution:

Before applying to the entire surface, test the product on a small area to check for colour changes.

Do not apply the product externally if rain is forecast.

Does not protect against acidic aggression.