



OIL STAIN REMOVER

NO SPOT

NATURAL STONE, GRANITE, MARBLE, CONCRETE, QUARRY TILE, AGGLOMERATES, TERRACOTTA



WHAT IT'S FOR

- Removes absorbed oil stains.
- Extracts grease from indoor and outdoor wall and floor coverings.
- Deeply cleans grease and oil from cracks, where other stain removers can't reach.
- Ideal for natural stone, marble, granite, concrete, agglomerates, quarry tile and terracotta.
- Excellent for kitchens and driveways.

ADVANTAGES

- Easy-to-use: just spray and wipe.
- Highly effective on treated and untreated outdoor natural stone and terracotta.
- Leaves no trace when used on fresh stains.
- Effectively cleans untreated surfaces.

HOW TO USE IT

READY TO USE, no dilution required. Spray **NO SPOT** directly on the stain from a 6-inch (15 cm) distance, keeping the can at a 45° angle. Let dry for a few minutes, until a white powder is formed. The product absorbs grease deposits and dries. Brush away the white powder residue and wipe with a wet cloth. For stubborn stains, repeat the application if necessary.

Caution: For waxed floors, completely remove the wax from the surface. After removing the stain, reapply the wax.

Storage temperature: between 32°F and 86°F (0°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).



Packaging:

8.5 OZ (250 ml) 12 spray cans per box

Data sheets are subject to change without notice. Revision date: 2024/04/18 - REV. 01

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over
200 INTERNATIONAL TOP BRANDS
manufacturers of materials for floors and wall coverings

filasolutions.com