

## STRONG ACID DE-SCALER

TERRACOTTA, QUARRY TILES, PORCELAIN TILES



### WHAT IT'S FOR

- Removes dirt and building-site residues.
- Eliminates any saline efflorescences.
- Cleanses and removes deposits.
- It is essential for terracotta when other normal buffered acids for deposit removing are not effective.

### ADVANTAGES

- Contains biodegradable ingredients
- Buffered acid, does not produce harmful fumes for the user and the environment: it does not contain hydrochloric acid.
- It has longer working time than pure acids which have an instant reaction and limited performance time.
- It's ideal for applying on vertical surfaces due to its viscosity.
- It removes deposits and cleans at the same time because it also contains surfactants.

### HOW TO USE IT

**Dilution:** between 1:5 and 1:10 according to the level of dirt to be removed.

**Application:**

**For residues from laying floors:** on porous materials such as terracotta and stone, wet the surface well with water before washing. Depending on the extent of the deposits to be removed, dilute 1 litre of **PHZERO** in 5 or 10 litres of water. Spread the solution thus obtained over the surface, leaving it to take effect for 4–5 minutes. Next, use a floor brush or single-disc machine, collecting all residues with a cloth or liquid vacuum cleaner. Rinse with plenty of water.

**For walls and vertical surfaces:** before washing, we recommend wetting the surface thoroughly with water. Use a brush to apply the product undiluted. Leave the product to take effect for 4–5 minutes then rub with a suitable tool and rinse well, preferably using a water jet cleaner.

**Caution:**

**PHZERO** is a highly concentrated product, please only use when the level of dirt requires it.

Do not use **PHZERO** on marble and in general on materials that are sensitive to acids. Before applying the product, we recommend testing its reaction on a small area of the surface.



### COVERAGE

**APPROXIMATE COVERAGE AND DILUTION (1 litre):**

Terracotta 1:5	20 m <sup>2</sup>
Porcelain tiles 1:5	40 m <sup>2</sup>

"Coverage shown is for guidance purposes only and refers to single coats"

**Packaging**

5 litres: boxes of 4.

**WARNINGS**

- Keep out of reach of children.
- Do not disperse into the environment after use.

**TEMPERATURES**

Storage temperature: from 5° to 30° C.  
The product should be applied to materials with temperature between 5° and 30° C.