



PROFESSIONAL ANTI-SLIP TREATMENT



PROGR1P

PORCELAIN TILES, CERAMIC TILES, SILICEOUS STONES SUCH AS GRANITE, QUARRY TILE



WHAT IT'S FOR

- Increases slip resistance on damp or wet floors.
- Increases the surface's friction coefficient.
- Creates a microporous surface on the treated material.
- Reduces the risk of slipping on floors when walking with shoes or barefoot.
- Treatment for professional use.

ADVANTAGES

- Non-film-forming, leaves no residue.
- Quick acting
- Does not change the appearance of the material.

HOW TO USE IT

Dilution: ready to use.

Application:

1. Determine the contact time

Given the diversity of materials, the most suitable contact time must be determined by running a test on an uninstalled tile or on a small, inconspicuous area. Protect the adjacent materials and areas not being treated.

PROGR1P takes effect after just one minute. After running the 1-minute test, if more time is required the test may be repeated with progressively longer contact times.

2. Prepare the surface

Prepare the surface for treatment by washing according to the type of dirt on the surface (e.g. **DETERDEK PRO** for limescale or cement grout haze, or **PS87 PRO** for organic dirt or film caused by improper maintenance).

For easier application, split the surface into areas between 10 and 32 sq. ft. delimiting the area at the joints.

3. Application

Apply **PROGR1P** to a clean, dry surface using a lambswool applicator or white pad and leave for the determined contact time, ensuring the surface stays wet throughout. Then clean with a wet vac or remove the residue with a cloth or mop. Rinse thoroughly with water and move to the next area.

It is important to apply the product to all areas being treated for the same length of time and with the same method in order to achieve even results.

After treatment, we recommend a neutralizing wash using **CLEANER PRO** 1:200 (1 1/2 tablespoons of product per gallon of water) and a white pad on the entire treated surface.

Caution: The treatment is irreversible: a preliminary test is strongly recommended. The treatment may alter the gloss of the surface. If used incorrectly, the product can lead to a loss of color. The product is corrosive on glass. Use the product at surface temperatures between 10° and 30°C. Do not treat surfaces when they are exposed to direct sunlight. The anti-slip treatment may be ineffective and uneven on porcelain with a polished or lappato finish. Do not use on calcareous stone.

Storage temperature: between 41°F and 86°F (5°C and 30°C).

Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

- ▶ INCREASES THE SURFACE'S FRICTION COEFFICIENT
- ▶ IMMEDIATE ACTION, DOES NOT FORM A SURFACE FILM
- ▶ PROFESSIONAL USE



Coverage:

16.9 FL.OZ. (500 mL)
32 sq. ft. (3 m²)

Coverage rates are indicative.



Packaging:

16.9 FL.OZ. (500 mL) 6 plastic bottles per box

Data sheets are subject to change without notice. Revision date: 2026/03/27 - REV. 00

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over
240 INTERNATIONAL TOP BRANDS
manufacturers of materials for floors and wall coverings

filasolutions.com