

DETERGENT



ROBOSHINE CONCENTRATED CLEANER FOR ROBOT MOPS AND VACUUM MOPS

ALL MATERIALS

- Suitable for all types of robot mops and vacuum mops
- Multipurpose cleaner: ideal for cleaning all types of hard surfaces
- Does not foam when diluted according to the instructions
- Fast-drying
- High coverage: up to 100 washes (concentrated cleaner savings)
- Refreshes the air and prevents unpleasant odours from forming in the tank and on the brushes
- Hampers the build-up of limescale in the water tank
- Does not damage fabrics and upholstery upon contact
- Delicate spring scent: makes cleaning more pleasant
- Delicate formula: does not interfere with the operation of the robot mop and vacuum mop components

WHAT IT'S FOR

- Clean all hard surfaces.
- Effectively removes dirt and stains without leaving a residue
- Formula specifically developed for robot mops and vacuum mops: low foaming for easier and deeper cleaning
- Also suitable for waxed floors

HOW TO USE IT | 1 CAPFUL = 10 ml

Dilute 1 capful (10 ml) of **ROBOSHINE** in up to 300 ml of water (see robot mop/vacuum mop scrubber tank capacity).

Insert a capful of the product directly into the water tank and fill the tank to its maximum capacity. Dampen brushes or floor cloths with water before installing them on the machine, then begin washing the floor.

Caution:

Follow the instructions in the user manual on how to use the robot mop cleaner or vacuum mop. The cleaner can be diluted with demineralised water, should this be recommended by the manufacturer.



| PACKAGING | PIECES PER CARTON | INDICATIVE COVERAGE AND DILUTION |
|-----------|-------------------|--|
| 1L | 6 pz | High coverage: up to 100 washes |
| | | Tank up to 300 ml: 1 capful |
| | | 300 to 500 ml tank: 1-2 capfuls |
| | | 1 lt tank: 4 capfuls |
| | | For larger tanks dilute the product 1:20 |
| | | 2/3 lt tank: half a glass* |
| | | 4/5 lt tank: one glass* |

* 1 standard table glass = 200 ml..

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.

TEMPERATURES

Storage temperature: from 5° to 30° C.
The product should be applied to materials with temperature between 5° and 30° C.