

THE ANTI-SEEPAGE BREATHABLE CONSOLIDATING AGENT

**PORCELAIN TILES, MARBLE AND STONE,
AGGLOMERATES, CONCRETE, TUFF,
TERRACOTTA, QUARRY TILES**



FORMULATED WITH ETHYL SILICATE: The product penetrates into fissures and bonds chemically with the material, making it more compact and durable. This technology ensures excellent resistance to UV rays and the natural ageing process.



COVERAGE

APPROXIMATE COVERAGE (1 litre):

Terracotta, Stone	10/15 m ²
Porcelain tiles, Quarry tiles	30 m ²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1 litre: boxes of 12.
5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.

TEMPERATURES

Storage temperature: from 0° to 30°C.
The product should be applied to materials with temperature between 5° and 30°C.

WHAT IT'S FOR

- Protects terracotta, quarry tiles, porcelain tiles, concrete and natural stone from water and damp.
- Penetrates into materials strengthening the surface.
- Removes any water seepage problem.
- Prevents water seepage, and formation of mould and efflorescence and consequently any serious structural issues.
- Protects grout joints.
- Penetrates into small cracks (from 0.5 µm to 1 mm) making them water repellent.

ADVANTAGES

- It does not form surface film and allows treated materials to breathe.
- Easy to use because it is ready to apply.
- Does not yellow with ageing or with any environmental condition.
- Provides high coverage.

HOW TO USE IT

No dilution required: ready to use.

Application: On a dry and clean surface (for deep cleaning, use the **FASE ZERO** detergent), apply **SALVATERRAZZA** evenly on the entire surface using a fleece pad or a different application method, taking care to impregnate the gaps and fissures thoroughly. Before the product dries (within 10 minutes), remove any residues by dabbing the surface with a clean cloth, being careful not to leave any traces of the product. Applying an abundant amount of product does not improve its performance. On absorbent materials such as natural stone, agglomerates, concrete and bricks, apply two coats of the product with an 8-hour interval in between, following the above-mentioned instructions. To speed up the process, the surface can be treated with a single-disc floor scrubber. The surface can be walked on after 8 hours. The protection takes effect after 24 hours.

Maintenance: use a diluted solution of **CLEANER PRO**.

FOR PROFESSIONAL USE ONLY: spray the product (airless system) on vertical surfaces until they are saturated and use appropriate PPE, as specified in the safety information sheet.

Caution:

The product may brighten the material, so we recommend testing its reaction beforehand on a small area. Do not apply the product externally if rain is forecast. Does not protect against acidic aggression.