



SATIN-EFFECT PROTECTIVE WAX

**TERRACOTTA, QUARRY TILES, NATURAL STONE,
UNPOLISHED AGGLOMERATES, CONCRETE,
CONCRETE TILES**



WHAT IT'S FOR

- Ideal both for treatment and maintenance
- Protects unpolished natural stones (limestone, slate, etc.), red stoneware, non-vitrified quarry tiles and various types of terracotta
- Recommended for treating floors made of: slate, manufactured stone and cement tiles
- Highly recommended for maintenance of marble and natural stone with brushed finish

ADVANTAGES

- A 3-in-one solution: protects, maintains and gives floors an excellent finish
- Original new satin look
- Ideal to create prestigious floors: enhances the beauty of the surface
- Easy to apply and maximum coverage
- Does not degenerate with maintenance

HOW TO USE IT

Dilution: either undiluted or diluted according to requirements.

For protecting surfaces: using fleece or other applicator, apply an even coat of the product on the clean and dry floor. After 1 hour, apply a second coat at right-angles to the first. The floor can be walked on after roughly half an hour. When treating highly absorbent materials, we recommend applying a coat of **FOB XTREME** or **W68** beforehand. Wait 24 hours before applying **SATIN**.

Renewal of the finish (every 2-3 months): after having cleaned the surface with a diluted solution of **CLEANER PRO** (1:200), apply **SATIN** by diluting 500 ml of product in 5 litres of water. The floor can be walked on once dry.

Restoration of the protection: remove the wax from the surface using the **PS87 PRO** detergent, diluted 1:5. Rinse the surface. Apply the undiluted wax on the dry floor using fleece or other applicator. No need to polish.

CLEANING OF TOOLS: clean with water after use.

For ordinary maintenance: use a diluted solution of **CLEANER PRO** (1:200)

Caution:

*Do not walk on floor while it's drying and do not repeat application on treated areas which are not yet dry.
To remove this wax, use the specific wax-remover **PS87 PRO**.
Do not use the product on external surfaces, in damp environments and where water puddles may form (bathrooms, showers).
The product can change the appearance of the material, first spot test a small surface area to check for any changes.*



COVERAGE

COVERAGE (1 litre):

Terracotta	30 m ²
Stone	30/40 m ²

Coverage shown is indicative and refers to single coats

Packaging

- 1 litre: boxes of 12.
- 5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- The product is sensitive to frost: store it as indicated on the label.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.