



MATTE FINISH PENETRATING ENHANCER & SEALER

STONEPLUS

ALL NATURAL STONE

SOLVENT TECHNOLOGY



WHAT IT'S FOR

- Enriches the color of polished, honed, textured and tumbled natural stone.
- Highlights the natural surface character.
- Protects the surface from dirt, water and oil stains.
- Enhances and intensifies the stone's natural color with a matte finish.
- Excellent protection for countertops, inlays and backsplashes.
- Hides cracks on granite surfaces.

ADVANTAGES

- Ideal for indoor and outdoor surfaces.
- Does not form a film or yellow over time.
- UV resistant.
- Long lasting protection.
- Provides very high coverage rates.

HOW TO USE IT

READY TO USE, no dilution necessary. Apply **STONEPLUS** to a clean, dry surface using a paintbrush or other suitable applicator. Wait up to 10 minutes, then rub the surface to allow the product to completely penetrate, until any excess residue is wiped off. Do not allow excess to dry completely on the surface. Remove any residue by rubbing the surface with a cloth soaked in **STONEPLUS**. If residue is not removed, the surface will remain sticky. If rubbing the surface with a cloth soaked in **STONEPLUS** does not work, use mechanical action or a stripper. Denser materials will require maximum time to penetrate the surface. The surface may be used for normal foot traffic after 8 hours. Full cure and maximum sealer protection is achieved in 24 hours. For deeper, more intense color, apply 2-3 coats; wait at least 8 hours between coats.

Caution: Once the surface has been treated with **STONEPLUS**, the treatment cannot not be reversed; the stone cannot return to its original state. Before full application, test the product on a small, inconspicuous area or loose sample. On some materials installed outdoors, we recommend reapplying the product annually to maintain the optimal enhancing effect. The product does not protect against acid stains. Do not apply the product outdoors if rain is in the forecast. Apply and leave the product to dry in a well ventilated area. Keep the product in a cool, dry place.

Storage temperature: Between 32°F and 86°F (0°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

- ▶ **STAIN PROTECTION FOR POROUS AND NON-POROUS STONE**
- ▶ **UV RESISTANT AND NON-YELLOWING**
- ▶ **INTERIOR AND EXTERIOR USE**
- ▶ **WORKING PROPERTIES:**
SURFACE TRAFFIC = 8 HOURS
FULL CURE = 24 HOURS



Coverage:

1 QT (0.95 L)

Polished stone >

510 sq.ft. (47 m²)

Natural finish stone >

205-259 sq.ft. (19-24 m²)

Coverage rates are indicative and per coat.



Packaging:

1 PT (473 ml) 12 plastic bottles per box

1 QT (946 ml) 6 plastic bottles per box

Data sheets are subject to change without notice. Revision date: 2024/07/30 - REV. 03

Fila Chemicals USA, Corp.
Miami, FL 33172
tel +1-305-513-0708
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over
200 INTERNATIONAL TOP BRANDS
manufacturers of materials for floors and wall coverings

filasolutions.com