STONEPLUS ECO





COLOUR-ENHANCING PROTECTIVE AGENT

NATURAL STONE. MARBLE. GRANITE



STONEPLUS ECO penetrates deeply into the material and protects it extensively from watery or oily stains and dirf. It also revives grout lines, does not yellow or form a surface film, and withstands UV radiation.



COVERAGE

30/50m²
15/25m²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

375 ml: boxes of 12. 1 litre: boxes of 6. 5 litres: boxes of 4.

WARNINGS

- When used indoors, it is advisable to adequately aerate the room to facilitate drying.

 Store the product in a cool dry place.

 Outdoor flooring must be properly laid before being treated and must satisfy all the specific requirements, including: adequate sloping, properly executed expansion joints, perfect isolation from the underlying ground, proven compatibility with sub-zero temperatures.

TEMPERATURES

ILIMFERALUAES
Storage temperature: from 5° to 30° C
This product must be applied to surfaces with temperature between 10°C and 30°C.

WHAT IT'S FOR

- · Colour-reviving protector.
- · Protects and revives the original colour of polished, untreated and tumbled natural stone.
- Penetrates deep down into the material and reduces dirt absorption.

ADVANTAGES

- · Produces a reviving effect on all finishes.
- · Product with extremely low VOC emissions, helps to gain Leed Credits in accordance with the U.S. and Italian protocols.
- · Water-based: eco-friendly treatment
- · Being a water-based product, it withstands residual humidity conditions and can therefore be applied a few days after the initial wash, making treatment guick.
- It also revives grouting, does not yellow or form a surface film, and withstands UV radiation.
- · Does not form surface film.
- · Treated surfaces are safe for food contact
- An A+ classified product in accordance with the French VOC regulation

HOW TO USE IT

No dilution required: ready to use.

Application: Wet the dry and clean surface completely with STONEPLUS ECO using a brush, sponge or other application tool. Rub with a sponge or cloth during application to favour the product's absorption, and thoroughly remove any excess product. The surface can be treaded after just 4 hours. Remove any residues from the surface using a cloth wetted with STONEPLUS ECO and rub. For improved protection, the treatment should be completed with MP90 ECO XTREME within 4 hours.

Routine maintenance:

REFRESH for tops, window sills and tables or **CLEANER PRO** diluted 1:200.

Once treated with STONEPLUS ECO, the stone cannot be restored to its original condition. Before treating the surface, carry out a spot test to check the final colour. Do not apply the product if rain is expected. Does not protect against acidic aggression.