

DIRT REPELLENT



STOP DIRT

TEXTURED PORCELAIN TILES, UNPOLISHED PORCELAIN TILES,
LAPPATO PORCELAIN TILES



WHAT IT'S FOR

- Makes cleaning quick and easy.
- Improves the material's resistance to dirt.
- Maintains the original appearance of the material over time.

ADVANTAGES

- Provides prolonged protection over time.
- Interior and exterior use.
- High coverage.
- Does not alter the material's slip resistance (tests conducted in conformity with B.C.R.A. and ASTM C 1028-2007 methods).
- Does not form surface film.
- UV resistant and non-yellowing.

HOW TO USE IT

READY TO USE, no dilution necessary.

Application for new surfaces:

1. Wash the floor thoroughly using **DETERDEK** (for cement-based grouts) or **EPOXYOFF** (for epoxy grout).
2. Apply **STOP DIRT** to a clean and dry floor also treating the grout, covering evenly with a fleece or other suitable applicator.
Advice from the experts: Given the product's high coverage, apply a moderate quantity of product to treat 79-118 inches (2-3 m²) of surface area at a time.
3. Rub the surface with a cloth or single-disc machine with white disc.
4. Fully remove all product residues within 10 minutes, either manually using a microfiber cloth or with a single-disc machine.
5. After at least 12 hours, before walking on the treated surface, remove any product residues using a clean microfiber cloth.

Application on untreated surface to be restored:

1. Wash the floor using **PS87** and/or **DETERDEK**.
2. Apply **STOP DIRT** on the dry surface in the manner described above.

Caution: The product may enhance the color of the material or grouting; carry out a spot test on a small surface area before full application.
Aerate rooms during use. Do not apply to matt finish Lappato porcelain tiles.

Storage temperature: Between 32°F and 86°F (0°C and 30°C).
Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

MAKES CLEANING EASY.

IT DOES NOT ALTER THE SLIP RESISTANCE OF SURFACES.

Working Properties:

Surface Traffic = 12 hours
Full Cure = 24 hours



Coverage:

1.05 QT (0.95 L)
Textured, natural and Lappato porcelain tiles >
753 sq.ft. (70 m²)
Coverage rates are indicative and per coat.



Packaging:

16.9 OZ (500 mL) 12 plastic bottles per box