

# ULTRASHINE FLOOR



## PROFESSIONAL CRYSTALLISER

**POLISHED MARBLES, POLISHED AGGLOMERATES,  
POLISHED LIMESTONE SURFACES**



### WHAT IT'S FOR

- Professional product for restoring the sheen of worn surfaces.
- Keeps surfaces shiny and resists wear caused by foot traffic.
- Ideal for the crystallisation of polished limestone surfaces (marble, travertine) and polished agglomerates (terrazzo, traditional Palladian and Venetian terrazzo).

### ADVANTAGES

- Quickly restores over 90% of its original shine (average value obtained through laboratory testing).
- High coverage: 50-70 m<sup>2</sup>/1L depending on the initial condition of the material.
- Maintains surfaces shiny over time and increases their resistance to foot traffic.
- The treatment may be reapplied on the entire surface or on specific areas.



### COVERAGE

**With one litre of product:**

**depending on the initial condition  
of the material: 50-70 m<sup>2</sup>**

Coverage shown is indicative and refers to single coats.

### Packaging

5 litres: boxes of 4.

#### WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.

#### TEMPERATURE

Storage temperature: Between 5°C and 30°C.  
Must be applied at temperatures between 10°C and 30°C.

### HOW TO USE IT

#### No dilution required:

ready to use.

#### Application:

Shake before use and apply using an airless pump. On a clean, dry surface free of dirt, dust and wax residues, spray a moderate quantity of **ULTRASHINE FLOOR** on a small area (max 2 m<sup>2</sup>) then intervene immediately using a single-disc floor scrubbing machine fitted with a stainless steel wool disc, spreading the product evenly. Proceed with the operation until the product has dried completely and the desired sheen has been attained. Repeat the procedure for the rest of the surface to be treated. Remove the steel wool fibres by wiping the surface with a microfibre cloth or dry microfibre mop.

#### Caution:

*The product is for professional use only.*

*Do not leave standing water on the surface or allow the product to drip on the surface from the container.*

*Do not use on non-limestone surfaces such as granite, quartzite or sandstone in general.*

*Avoid contact with materials such as wood, terracotta, ceramic and metal (trims in steel and aluminium).*

*Carry out a spot test before application to check the effect of the treatment.*

*We suggest polishing the surface with a white pad to uniform the sheen and eliminate any marks of the application.*

*Wait at least 24 hours before wetting the floor.*