

STAIN PROTECTOR FOR UNPOLISHED SURFACES

UNPOLISHED STONE AND AGGLOMERATES, TERRACOTTA, QUARRY TILES, CONCRETE



W68 is a water-based product that can also be applied to surfaces with residual moisture.



COVERAGE

COVERAGE (1 litre):

Terracotta rustic Tuscan, polished 15-20 m²

Concrete, handmade, Spanish, Terracotta hollow tile, brick 7-10 m²

Stone 10-20 m²

Coverage shown is indicative and refers to single coats

Packaging

1 litre: boxes of 12.

5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Protect can from frost. Store at room temperature.
- Outdoor flooring must be properly laid before being treated and must satisfy all the specific requirements, including: adequate sloping, properly executed expansion joints, perfect isolation from the underlying ground, proven compatibility with sub-zero temperatures.

TEMPERATURES

Storage temperature: from 5° to 30° C.

This product must be applied to surfaces with temperature between 10°C and 30°C.

WHAT IT'S FOR

- Seals and protects porous materials such as untreated natural stone, terracotta and concrete from oily dirt
- Stain-proofing: it hampers the absorption of common watery and oily stains
- Suitable for interior and exterior surfaces
- For use on interior floors as a protective base-coat before the application of wax
- It provides an anti-graffiti protection that prevents graffiti paint from bonding to surfaces. It speeds the cleaning process because graffiti can be easily removed

ADVANTAGES

- Natural finish: does not alter the surface's original appearance.
- A water-based product free of hydrocarbon solvents, which makes the treatment more eco-friendly and drastically reduces the treatment times as it can be applied to surfaces with residual moisture.
- Does not form surface film
- Does not alter terracotta frost resistance.
- Excellent also for concrete surfaces.
- An A+ classified product in accordance with the French VOC regulation
- A product certified according to EMICODE EC1 Plus and LEED (ACP)
- A VOC-free product with a low environmental impact and **INDOOR AIR COMFORT GOLD** certificate*

* The product has passed the applicable stringent requirements and conforms to all compulsory national standards (for example: French A+, CAM Edilizia, AgBB/ABG, Belgian Regulation, etc.) as well as innovative environmental sustainability criteria such as LEED (ACP), BREEAM, WELL. For further information consult: <https://www.filasolutions.com/eng/company/the-fila-research-centre>

HOW TO USE IT

No dilution required: ready to use.

Indoor surfaces consisting of terracotta and natural stone and concrete:

On a clean and dry surface, apply one coat of **W68** evenly, using a brush or fleece pad, while soaking the joints well. Wait 4 hours then apply a coat of the specific finishing wax for the desired aesthetic effect (**MATT** for a natural effect, **LONGLIFE** or **CLASSIC** for a polished effect, if available for sale). With absorbent materials, apply a further coat of reinforcement wax one hour after the first coat of wax. For maintenance with satin effect, apply one coat of **SATIN**.

Outdoor surfaces consisting of terracotta, natural stone and concrete:

On a clean surface, apply 2 coats of **W68** evenly, using a brush or fleece pad, also soaking the joints well. Remove any excess unabsorbed product by dabbing it with a micro-fibre cloth, before the product dries.

CLEANING OF TOOLS: clean with water after use.

For ordinary maintenance: use a diluted solution of **CLEANER PRO** (1:200)

Caution:

Since there are so many different materials, before applying the product we recommend testing it on a small area of the surface to check for any colour changes.

Do not apply the product outdoors if rain is in forecast. Does not protect against acid aggression.