

CONSOLIDATING PROTECTIVE PRODUCT WITH WET EFFECT

UNFINISHED MARBLE AND GRANITE,
UNPOLISHED NATURAL STONE AND
AGGLOMERATES, TUFF



WHAT IT'S FOR

- Gives wet look to untreated surfaces (tumble finishes, flame finishes, natural sawn finishes).
- Protects material from water and oil.
- Consolidating effect treatment.

ADVANTAGES

- Provides a wet effect that can be intensified with several applications.
- Does not yellow with ageing or with any environmental condition.
- Does not scrape from surface.

The product can also be used to revive and protect masonry kitchens profiles, fret designs of coalings, rosettes, tumbled marble and any interior or exterior coarse stone surface. **WET** does not yellow over time nor does it shed its film.



COVERAGE

With one litre:

10/20 m²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1 litre: boxes of 12.
5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- If used indoors, it is advisable to ventilate the area well.
- The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.
- Outdoor flooring must be properly laid before being treated and must satisfy all specific requirements, including: adequate sloping, properly executed expansion joints, perfect insulation from underlying ground, proven compatibility with sub-zero temperatures.

TEMPERATURES

Storage temperature: from 0°C to 30°C
The product should be applied to materials with temperature between 5° and 30°C.

HOW TO USE IT

No dilution required: ready to use. Application: 1. On a clean and dry surface, apply one even and continuous coat of **WET** with a brush. 2. After 24 hours repeat treatment in the same way. 3. For very absorbent materials, a third coat may be required to reach the desired wet effect. Maintenance: diluted solutions of **CLEANER PRO**. In the areas most exposed to weather conditions we recommend applying the product again every two years.

Caution:

*do not apply the product externally if rain is forecast during the following 24 hours. Do not walk on floor while it's drying: wait 24 hours after last product application. Do not apply on terracotta floors or polished/very smooth surfaces. If product has been wrongly applied or if a thorough cleaning is required, remove **WET** using **NOPAINT STAR**.*

The product cannot be applied on supports subject to rising damp and in damp environments where water tends to stagnate (showers, saunas, Turkish baths, etc.).