


# WET LOOK SEALER



**WET**

**UNPOLISHED NATURAL STONE**

**SOLVENT TECHNOLOGY**



## WHAT IT'S FOR

- Intensifies the color of unpolished natural stone.
- Gives surfaces a wet-look, glossy finish.
- Protects surfaces from dirt and stains.
- Prevents the penetration of water, grease and oil.
- Ideal for use in kitchens, under barbeques, on driveways and in high traffic areas.

## ADVANTAGES

- Does not yellow or flake over time.
- UV resistant.

## HOW TO USE IT

Ready to use, no dilution necessary.

Apply an even, continuous coat of **WET** on a clean, dry surface with a large, flat paintbrush, lambswool applicator or roller. Wait 24 hours and apply a second coat, using the same method. For particularly porous materials a third coat may be needed to achieve the desired wet-look effect.

**Caution:** Wait 24 hours after the application of the last coat before walking on the surface. Do not apply on terracotta floors or polished surfaces. Do not apply the product outdoors if rain is in the forecast. Use **PROSTRIP** to thoroughly clean treated surfaces or if the product has been applied incorrectly.

- **PROTECTS SURFACES AGAINST STAINS AND DIRT.**
- **HIGHLY RESISTANT TO UV RAYS AND HEAVY TRAFFIC.**



**Coverage:**  
Unpolished natural stone  
• 215 sq.ft. (20 m<sup>2</sup>)

*Coverage rates are indicative and per coat.*



**Packaging:**  
1 QT (946 ml) 6 plastic bottles per box