



# WET LOOK SEALER

## WET ECO

UNPOLISHED NATURAL STONE,  
UNPOLISHED AGGLOMERATES, TERRACOTTA



WATER-BASED  
TECHNOLOGY



- ▶ **HIGHLY RESISTANT FOR INDOOR AND OUTDOOR USE**
- ▶ **STAIN PROTECTION FOR UNPOLISHED SURFACES**
- ▶ **UV RESISTANT AND NON-YELLOWING**
- ▶ **WORKING PROPERTIES:**  
*SURFACE TRAFFIC = 12 HOURS*  
*FULL CURE = 24 HOURS*



### Coverage:

1 QT (0.95 L)

**Unpolished natural stone, unpolished agglomerates ›**

100-205 sq.ft. (9-19 m<sup>2</sup>)

**Terracotta ›**

75-205 sq.ft. (7-19 m<sup>2</sup>)

*Coverage rates are indicative and per coat.*



### Packaging:

1 QT (946 ml) 6 plastic bottles per box

## WHAT IT'S FOR

- Seals indoor and outdoor unpolished natural stone, unpolished agglomerates and terracotta.
- Gives the surface a wet-look, glossy finish.
- Protects surfaces from dirt and stains.
- Intensifies the color of unpolished natural stone.
- Ideal for use in kitchens, under barbecues, on driveways and in high traffic areas both indoors and outdoors.

## ADVANTAGES

- Eco-friendly: water-based.
- Weather resistant.
- Is not affected by residual humidity: can be applied 24-48 hours after initial cleaning.
- Resistant to heavy traffic.
- Does not flake or yellow over time.
- Makes cleaning easier.
- Does not alter the frost resistance of terracotta.
- A plant-based product: developed using raw materials of organic origin and renewable resources.
- Certified **INDOOR AIR COMFORT GOLD\***: contains very low VOC emissions with low environmental impact. Contributes towards LEED credits.

**\*WET ECO passed rigid requirements to ensure compliance with the low VOC emissions required by international protocols. Products certified Indoor Air Comfort Gold are those with the lowest VOC emissions in their class, hence good for indoor air quality. Indoor Air Comfort Gold certificates are directly accepted as proof from programs for sustainable buildings such as BREEAM New Construction and LEED.**

## HOW TO USE IT

**READY TO USE**, no dilution necessary. Shake before use. The surface must be completely clean before application. Apply an even coat of **WET ECO** to clean, dry floors using a large, flat paintbrush, lambswool applicator or roller, rubbing into the grout joints. Do not allow excess product to sit on the surface. Apply a second coat of the product 2-3 hours after the first coat following the same method. The surface may be used for normal foot traffic after 12 hours. Full cure and maximum sealer protection is achieved in 24 hours.

**Caution:** Do not apply the product on humid surfaces or surfaces with moisture rising through the substrate. Do not apply the product outdoors if rain is in the forecast. Use **PROSTRIP** if the product has been applied incorrectly. The product does not protect surfaces from acid stains. Do not use on polished surfaces. Do not use on treated surfaces.

**Storage temperature:** Between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 50°F and 86°F (10°C and 30°C).

Data sheets are subject to change without notice. Revision date: 2024/07/30 - REV. 03

Fila Chemicals USA, Corp.  
Miami, FL 33172  
tel +1-305-513-0708  
filausa@filasolutions.com

TOLL FREE 1-844-FILA123



Recommended by over  
**200 INTERNATIONAL TOP BRANDS**  
manufacturers of materials for floors and wall coverings

filasolutions.com