

WET-LOOK COLOUR ENHANCING PROTECTOR

UNPOLISHED NATURAL STONES, UNPOLISHED AGGLOMERATES, TERRACOTTA



Prevents surfaces from flaking. **WET ECO** withstands traffic: it can be used on outdoor areas subject to vehicle traffic, near barbecues and kitchens.



COVERAGE

With one litre:

Unpolished stones and agglomerates 10/20 m²

Terracotta 7/20 m²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1 litre: boxes of 12.

5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Outdoor flooring must be properly laid before being treated and must satisfy all specific requirements, including: adequate sloping, properly executed expansion joints, perfect insulation from underlying ground, proven compatibility with sub-zero temperatures.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

WHAT IT'S FOR

- Stain protector and anti-dirt product with wet effect for unpolished natural stone surfaces, unpolished agglomerates and terracotta.
- Prevents the absorption of stains and facilitates dirt removal.
- It is particularly suited for exterior use and also effective for interiors.
- Prevents surfaces from flaking.

ADVANTAGES

- Eco-friendly treatment: water-based
- High resistance to intense traffic.
- Resistant to weathering.
- Does not peel nor yellow.
- Facilitates subsequent maintenance.
- Does not alter the frost resistance of terracotta (UNI EN ISO 10545-12).
- A plant-based product: developed using raw materials of organic origin and renewable resources
- A VOC-free product with a low environmental impact and INDOOR AIR COMFORT GOLD certificate*

* A VOC-free product with a low environmental impact and INDOOR AIR COMFORT GOLD certificate. The product has passed the applicable stringent requirements and conforms to all compulsory national standards (for example: FrenchA+, CAM Edilizia, Belgian Regulation, AgBB, etc.) as well as innovative environmental sustainability criteria, such as LEED, BREEAM, WELL. For further information consult www.filasolutions.com/ita/azienda/ricerca-e-sviluppo

HOW TO USE IT

No dilution required: ready to use.

Application: Shake before use.

Apply **WET ECO** evenly and continuously to a clean and dry surface using a flat paintbrush or fleece pad, wetting the grout lines as well. Apply a second coat of the product 2-3 hours later following the same method. Wait at least 12 hours before walking on the surface.

Maintenance: diluted solution of **CLEANER PRO**.

Caution:

For surfaces with low absorbency (slate, Botticino or Carrara marble) we recommend diluting the product with water (1 litre of product to 1 litre of water). Do not use on polished surfaces. Do not apply the product externally if rain is forecast.

The product cannot be applied to supports with problems connected with rising damp. If the product has been applied incorrectly or if thorough cleaning is required, remove **WET ECO** using **NOPAINT STAR**.