WET STONE ECO

WET LOOK CONSOLIDATING SEALER



ROUGH TEXTURED NATURAL STONE AND AGGLOMERATES (solit face, tumbled, flamed,

WATER-BASED

TECHNOLOGY

elc.). TUFF

WHAT IT'S FOR

- · Gives an enhanced, wet look to rough textured natural stone surfaces (split face, tumbled, flamed)
- · Protects the material against stains and dirt
- Prevents surface dusting

ADVANTAGES

- · Eco-friendly treatment: water-based
- · Particularly suited for exterior use; also effective in interiors
- · Stainproof and dirt repellent action
- Surface consolidating agent
- · High resistance to heavy traffic
- Resistant to weathering
- UV resistant and non-yellowing
- · Eases subsequent maintenance
- Provides a glossy enhanced look that can be intensified with additional coats



COVERAGE

With one litre:

10/20 m²

"Coverage shown is indicative and refers to single coats'

Packaging

1 litre: boxes of 12.

5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children. Do not disperse into the environment after use. In order to be treated, outdoor paving must be installed correctly and accor-ding to current installation regulations (UNI 11714-1 standard).

TEMPERATURES

Storage temperature: from 0° to 30°C. Must be applied at temperatures between 10°C and 30°C

HOW TO USE IT

No dilution required: ready to use.

Application: Shake before use.

On a clean, dry surface, apply WET STONE ECO evenly using a flat paintbrush, wax applicator, or microfibre pad, making sure to also impregnate the grout. To achieve the desired enhanced gloss effect on absorbent surfaces, apply a second coat once the first coat has dried (after 4 hours), following the above instructions.

For outdoor applications: we recommend applying the product once a year to maintain an optimal enhanced effect.

Wait at least 8 hours before walking on the surface.

Maintenance: diluted solutions of CLEANER PRO.

Caution:

Do not apply on materials with smooth, honed or polished finishes.

Test the product's aesthetic effect on a small, inconspicuous area of the surface before full application.

Do not apply the product outdoors if rain is forecast.

The product cannot be applied on substrates subject to rising damp and in humid environments with standing water (showers, saunas, Turkish baths, etc.).

If the product is applied incorrectly or to thoroughly deep clean the surface, remove WET STONE ECO using NOPAINT STAR.

Do not walk on the surface until it is completely dry.